


1 LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 SE 1/4 Section Number 6 Township Number T 29 S Range Number R 2 E
 County: Sedgwick
 Distance and direction from nearest town or city street address of well if located within city?

3 WATER WELL OWNER: McConnell AFB
 RR#, St. Address, Box # :
 City, State, ZIP Code : Wichita, Kansas
 Board of Agriculture, Division of Water Resources
 Application Number:

2 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 40.1 ft. ELEVATION: 1372
 Depth(s) Groundwater Encountered 1. 13.0 ft. 2. 17.29/88 ft. 3. 17.29/88 ft.
 WELL'S STATIC WATER LEVEL 10.08 ft. below land surface measured on mo/day/yr 11/29/88
 Pump test data: Well water was None ft. after 11/29/88 hours pumping 11/29/88 gpm
 Est. Yield 11 gpm: Well water was None ft. after 11/29/88 hours pumping 11/29/88 gpm
 Bore Hole Diameter 11 in. to 40.1 ft. and 11 in. to 40.1 ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 10
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded
 7 Fiberglass
 Blank casing diameter 2 in. to 9.8 ft. Dia 2.4 in. to 9.8 ft. Dia 2.4 in. to 9.8 ft. Dia 2.4 in. to 9.8 ft. Dia
 Casing height above land surface 2.4 in., weight 2.4 lbs./ft. Wall thickness or gauge No. Sch. 40

TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 9.8 ft. to 30.8 ft. From 30.8 ft. to 40.1 ft.
 GRAVEL PACK INTERVALS: From 5.9 ft. to 40.1 ft. From 40.1 ft. to 40.1 ft.

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Cement/Bentonite
 Grout Intervals: From 1.0 ft. to 3.1 ft. From 3.1 ft. to 5.9 ft. From 5.9 ft. to 5.9 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage unknown

Direction from well?			How many feet?		
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1.0	CLAY - DK Br Si Damp			
1.0	5.5	" - DK Br to Bl "			
5.5	13.0	" - Lt Rd Br Si "			
13.0	16.0	" - Greenish Gr w/ gravel Mt			
16.0	27.0	" - " Br Si Damp			
27.0	27.5	" - Rd Br w/ gravel Moist			
27.5	29.0	" - Greenish Gr Si Damp			
29.0	33.5	" - Lt Br Si "			
33.5	34.5	" - Orangeish Br w/ gravel layers			
34.5	39.5	Shale - Rd Br w/ Lt Br Si Cl wet			
39.5	40.1	" - Rd Br "			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/11/88 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 494 This Water Well Record was completed on (mo/day/yr) 11/19/88
 under the business name of Southwestern Lab by (signature) Robert J. Daniel