WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL

County: Sedgwick	Fraction: NE ¼ SE ¼ SW ¼	Section Number: 11	Township Number: T 28 S	Range Number: R 2 (E/W)

Distance and direction from nearest town or city? 5N 2W 1S of Rose Hill

Street address of well if located within city?

2 WATER WELL OWNER: Charles E Lame

RR#, St. Address, Box #: 1046 N Armour

City, State, ZIP Code: Wichita Kan 67206

Board of Agriculture, Division of Water Resources Application Number:

3 DEPTH OF COMPLETED WELL 100 ft. Bore Hole Diameter 8 1/2 in. to 14 ft., and ... in. to ... ft.

Well Water to be used as: 1 Domestic 2 Irrigation 3 Feedlot 4 Industrial 5 Public water supply 6 Oil field water supply 7 Lawn and garden only 8 Air conditioning 9 Dewatering 10 Observation well 11 Injection well 12 Other (Specify below)

Well's static water level 50 ft. below land surface measured on 7 month 25 day 80 year

Pump Test Data: Well water was 55 ft. after 1 hours pumping 30 gpm

Est. Yield 30 gpm: Well water was ft. after hours pumping gpm

4 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below)

Casing Joints: Glued X Clamped Welded Threaded

Blank casing dia 5 in. to 100 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 18 in., weight 200 lbs./ft. Wall thickness or gauge No 1214

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)

Screen or Perforation Openings Are: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)

Screen-Perforation Dia 5 in. to 80 ft., Dia in. to ft., Dia in to ft.

Screen-Perforated Intervals: From 60 ft. to 80 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

Gravel Pack Intervals: From ft. to ft., From ft. to ft.

From ft. to ft., From ft. to ft.

5 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grouted Intervals: From 0 ft. to 14 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Lateral lines 4 Cess pool 5 Seepage pit 6 Pit privy 7 Sewage lagoon 8 Feed yard 9 Livestock pens 10 Fuel storage 11 Fertilizer storage 12 Insecticide storage 13 Watertight sewer lines 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)

Direction from well W How many feet 200? Water Well Disinfected? Yes No

Was a chemical/bacteriological sample submitted to Department? Yes No: If yes, date sample was submitted month day year: Pump Installed? Yes No

If Yes: Pump Manufacturer's name Model No. HP Volts

Depth of Pump Intake ft. Pumps Capacity rated at gal./min.

Type of pump: 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other

6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on 8 month 10 day 80 year and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 257

This Water Well Record was completed on 9 month 8 day 80 year under the business name of Winter Well Drill by (signature) Charles Winter

7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



ELEVATION:

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	5	Soil			
5	15	Clay			
15	28	Clay/yellow			
28	35	Shale			
35	57	Lime			
57	80	Sandy Lime			
80	100	Lime			

Depth(s) Groundwater Encountered 1 70 ft. 2 ft. 3 ft. 4 ft. (Use a second sheet if needed)

INSTRUCTIONS: Use typewriter or ball point pen, *please press firmly* and *PRINT* clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Water Well Contractors, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY T 28 R 2 (E/W) SEC. 11 NE ¼ SE ¼ SW ¼