


1 LOCATION OF WATER WELL: County: Sedgewick Fraction: NN 1/4 SE 1/4 NE 1/4 Section Number: 17 Township Number: T 28 S Range Number: R 2 EW

Distance and direction from nearest town or city street address of well if located within city?
LOT 13 Heather Ridge Estates

2 WATER WELL OWNER: PAUL & RAUL
 RR#, St. Address, Box #: 4200 S. Cypress
 City, State, ZIP Code: Wichita, KS
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 94.47 ft. ELEVATION: 80 ft.
 Depth(s) Groundwater Encountered: 1 ft. 2. 80 ft. 3. 80 ft.
 WELL'S STATIC WATER LEVEL: 40 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was 20 gpm. Well water was 10 ft. after 20 hours pumping 20 gpm.
 Est. Yield: 20 gpm. Well water was 10 ft. after 20 hours pumping 20 gpm.
 Bore Hole Diameter: 10 in. to 10 in. and 10 in. to 10 in.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter: 8 in. to 8 in. Dia.
 Casing height above land surface: 12 in., weight 200 lbs./ft. Wall thickness or gauge No. 200
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 74 ft. to 94 ft., From 74 ft. to 94 ft., From 74 ft. to 94 ft., From 74 ft. to 94 ft.
 GRAVEL PACK INTERVALS: From 20 ft. to 94 ft., From 20 ft. to 94 ft., From 20 ft. to 94 ft., From 20 ft. to 94 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other: CLAY
 Grout Intervals: From 3 ft. to 20 ft., From 3 ft. to 20 ft., From 3 ft. to 20 ft., From 3 ft. to 20 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? How many feet? 75

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	dirt			
3	11	brown clay			
11	85	yellow clay & broken rock			
85	94	gray shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/6/55 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 1493 This Water Well Record was completed on (mo/day/yr) 8/25/58 under the business name of Reserres Well Drilling by (signature) Jerry Reserres