


1 LOCATION OF WATER WELL: County: Sedgwick		Fraction: NE 1/4 SW 1/4 SW 1/4	Section Number: 17	Township Number: T 28 S	Range Number: R 2 E/W
Distance and direction from nearest town or city street address of well if located within city? From 47th S. + Rock Rd. 1/4 N. 1/4 E. Buzzart add.					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 92 ft. ELEVATION: 83 ft. Depth(s) Groundwater Encountered 1. 83 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 42 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield 70 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 10 in. to ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No ☒ ; If yes, mo/day/yr sample was submitted Water Well Disinfected Yes ☒ No			
5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC Blank casing diameter 5 in. to 72 ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface +12 in. weight #200 lbs./ft. Wall thickness or gauge No.		5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued Clamped Welded Threaded			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)		SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)			
SCREEN-PERFORATED INTERVALS: From 92 ft. to 72 ft. From ft. to ft. From ft. to ft.		GRAVEL PACK INTERVALS: From 92 ft. to 13 ft. From ft. to ft. From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 13 ft. to 3 ft. From ft. to ft. From ft. to ft.		What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)			
Direction from well? North west		How many feet? Not built yet 100'			
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG			
92 83		Shale			
83 75		Red Bed			
75 40		Gray Shale			
40 36		Red Bed			
36 21		Gray Shale			
21 6		Brown clay			
6 0		earth			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) Feb 15, 1982 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 424 This Water Well Record was completed on (mo/day/yr) March 2, 1982 under the business name of Reiserer well drilling by (signature) Jerry Reiserer INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

E/W

SEC.

1/4

1/4

1/4