

LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Sedgwick	SE 1/4 SE 1/4 SW 1/4	29	T 28 S	R 2 E E/W

Distance and direction from nearest town or city street address of well if located within city?

8600 E. 63rd St. Wichita, Kansas

WATER WELL OWNER: Steve Timmermeyer	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: 3657 Payne	Application Number:
City, State, ZIP Code: Wichita, Kansas	

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	DEPTH OF COMPLETED WELL: 95 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 30 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 30 ft. below land surface measured on mo/day/yr 5-13-83 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 11 in. to ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC	7 Fiberglass	Cer-Mac styrene SDR-26	Threaded
3 RMP (SR)			
4 ABS			
Blank casing diameter 5 in. to 30 ft. Dia in. to ft. Dia in. to ft.			
Casing height above land surface 12 in. weight 1.59 lbs./ft. Wall thickness or gauge No. 203			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	8 RMP (SR)	11 Other (specify)	
2 Brass	9 ABS	12 None used (open hole)	
3 Stainless steel			
4 Galvanized steel			
5 Fiberglass			
6 Concrete tile			
SCREEN OR PERFORATION OPENINGS ARE:	8 Saw cut	11 None (open hole)	
1 Continuous slot	9 Drilled holes		
2 Louvered shutter	10 Other (specify)		
3 Mill slot			
4 Key punched			
5 Gauzed wrapped			
6 Wire wrapped			
7 Torch cut			
SCREEN-PERFORATED INTERVALS:			
From 30 ft. to 95 ft. From ft. to ft.			
GRAVEL PACK INTERVALS:			
From 14 ft. to 95 ft. From ft. to ft.			

GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
GROUT INTERVALS:	From 4 ft. to 14 ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	11 Fuel storage	15 Oil well/Gas well		
2 Sewer lines	12 Fertilizer storage	16 Other (specify below)		
3 Watertight sewer lines	13 Insecticide storage	None Apparent		
4 Lateral lines				
5 Cess pool				
6 Seepage pit				
7 Pit privy				
8 Sewage lagoon				
9 Feedyard				

Direction from well?	How many feet?
FROM TO LITHOLOGIC LOG	FROM TO LITHOLOGIC LOG
0 3 Topsoil	
3 31 Clay	
31 45 Fine Sand & Clay	
45 95 Clay	

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-13-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 5-13-83 under the business name of Harp Well & Pump Service, Inc. by (signature) M. Arnold
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.