

1 LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 NW 1/4 Section Number 29 Township Number T 28 S Range Number R 2 E/W
 County: Sedgwick
 Distance and direction from nearest town or city street address of well if located within city?

4th lot South of 55th St. South on Rock Road.

2 WATER WELL OWNER: LARRY WOLF
 RR#, St. Address, Box #: 410 WOLFE MACHINE INC
 City, State, ZIP Code: 1842 S. Mead Wichita, KS. Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 72 ft. ELEVATION: 60 ft.

Depth(s) Groundwater Encountered 1. 60 ft. 2. 60 ft. 3. 60 ft.
 WELL'S STATIC WATER LEVEL 12 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was 50 gpm: Well water was 50 ft. after 50 hours pumping 50 gpm
 Est. Yield 50 gpm: Well water was 50 ft. after 50 hours pumping 50 gpm
 Bore Hole Diameter 8 in. to 8 ft., and 8 in. to 8 ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well 12 Other (Specify below)
 Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted No
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded

Blank casing diameter 5 in. to 5 ft., Dia 5 in. to 5 ft., Dia 5 in. to 5 ft.
 Casing height above land surface 18 in., weight 160 lbs./ft. Wall thickness or gauge No. 160

TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 52 ft. to 72 ft., From 52 ft. to 72 ft., From 52 ft. to 72 ft.
 GRAVEL PACK INTERVALS: From 20 ft. to 72 ft., From 20 ft. to 72 ft., From 20 ft. to 72 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 20 ft., From 3 ft. to 20 ft., From 3 ft. to 20 ft.

What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage

Direction from well? How many feet? 70

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
<u>72</u>	<u>60</u>	<u>Shale</u>			
<u>60</u>	<u>53</u>	<u>Red bed</u>			
<u>53</u>	<u>32</u>	<u>Gray Shale</u>			
<u>32</u>	<u>5</u>	<u>Brown Clay</u>			
<u>5</u>	<u>0</u>	<u>Earth</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) June 28, 1984 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 4241 This Water Well Record was completed on (mo/day/yr) June 29, 1984 under the business name of Reisner Well Drilling by (signature) Jeff Reisner

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.