

1 LOCATION OF WATER WELL:					
County: <u>Sedgwick.</u> Distance and direction from nearest town or city street address of well if located within city?	Fraction: <u>SE ¼ NW ¼ NE ¼</u> <u>See Below</u> Section Number: <u>30</u> Township Number: <u>T 28 S</u> Range Number: <u>R 20 E/W</u>				
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :					
DENNIS MILLER 5721 JOEL LANE DERBY KS 67037	Board of Agriculture, Division of Water Resources Application Number:				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:					
A scale bar indicates 1 mile vertically and horizontally.					
4 DEPTH OF COMPLETED WELL..... ft. ELEVATION:					
Depth(s) Groundwater Encountered 1. <u>28</u> ft. 2. ft. 3. ft.					
WELL'S STATIC WATER LEVEL <u>28</u> ft. below land surface measured on mo/day/yr <u>2-9-91</u>					
Pump test data: Well water was ft. after hours pumping gpm					
Est. Yield .. <u>6</u> ... gpm; Well water was ft. after hours pumping gpm					
Bore Hole Diameter... <u>1 1/2</u> ... in. to <u>80</u> ... ft., and in. to ft.					
WELL WATER TO BE USED AS:					
☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) ☐ Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes.....No.. <u>X</u> ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes <u>X</u> No					
5 TYPE OF BLANK CASING USED:					
1 Steel 2 PVC Blank casing diameter in. to ft. Casing height above land surface weight lbs./ft. Wall thickness or gauge No. <u>SAB-26</u>	3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued <u>X</u> Clamped Welded Threaded.				
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 2 Brass SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter	3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 Gauzed wrapped 8 Wire wrapped 7 Torch cut 7 PVC <u>8 RMP (SR)</u> 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)				
SCREEN-PERFORATED INTERVALS:					
From <u>29</u> ft. to <u>80</u> ft.					
GRAVEL PACK INTERVALS:					
From <u>23</u> ft. to <u>80</u> ft.					
6 GROUT MATERIAL:					
GROUT INTERVALS: From <u>3</u> ft. to <u>23</u> ft.	1 Neat cement 2 Cement grout 3 Bentonite 4 Other				
What is the nearest source of possible contamination:					
1 Septic tank 2 Sewer lines 3 Watertight sewer lines	4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy <u>8 Sewage lagoon</u> 9 Feedyard				
Direction from well? <u>NW</u>					
How many feet? <u>100</u>					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top so. /			
2	24	clay			
24	80	Charcoal SHALE			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and completed on (mo/day/year) <u>2-9-91</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>318</u> . This Water Well Record was completed on (mo/day/yr) <u>2-15-91</u> under the business name of <u>Kramer & Pully</u> by (signature) _____					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					