

1) LOCATION OF WATER WELL: Fraction 1/4 NE 1/4 NW 1/4 NE 1/4 Section Number 35 Township Number T 28 S Range Number R 2 E/W

County: Sedgwick NE 1/4 NW 1/4 NE 1/4

Distance and direction from nearest town or city street address of well if located within city? 1/4 mile west of 143rd on S. side of 63rd

2) WATER WELL OWNER: Hanks Motors

RR#, St. Address, Box #: 1702 E. 47th S.

City, State, ZIP Code: Wichita, KS

Board of Agriculture, Division of Water Resources

Application Number:

3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4) DEPTH OF COMPLETED WELL: 83 ft. ELEVATION: 40 ft. below land surface measured on mo/day/yr Oct 17 88

Depth(s) Groundwater Encountered 1. 60 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 40 ft. below land surface measured on mo/day/yr Oct 17 88

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 15 gpm Well water was ft. after hours pumping gpm

Bore Hole Diameter 10 in. to ft. and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5) TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS Glued Clamped

1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded

2 PVC 4 ABS 7 Fiberglass Threaded

Blank casing diameter 10.5 in. to 200 ft. Dia. in. to ft. Dia. in. to ft.

Casing height above land surface 12 in. weight lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes

2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 63 ft. to 83 ft. From ft. to ft.

GRAVEL PACK INTERVALS: From 20 ft. to 83 ft. From ft. to ft.

6) GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 23 ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well

1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage

Direction from well? Down Slope How many feet? 75

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 2 earth

2 8 red gumbo

8 70 yellow clay water

70 83 grey - lime

7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) Oct 17 88 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 443 This Water-Well Record was completed on (mo/day/yr) Nov 28 88

under the business name of Reiser Well Drilling by (signature) Janis Reiser Brown