GSI Job No. 137416 MW-8 WATER WELL RECORD Form WWC-5 KSA 82a-1212 ID No. 0049493 1 LOCATION OF WATER WELL: Township Number Fraction Section Number Range Number NW 1/4 Neosho NW 1/4 32 28 20 R Distance and direction from nearest town or city street address of well if located within city? 434 N. Main St. – Erie 2 WATER WELL OWNER: Pete's Corporation RR#, St. Address, Box # : 1712 Broadway Board of Agriculture, Division of Water Resources Parsons, KS 67357 City, State, ZIP Code Application Number: LOCATE WELL'S LOCATON WITH 4 DEPTH OF COMPLETED WELL T DEPTH OF COMPLETED WELL

21 ft. ELEVATION: 896.99 (TOC)

Depth(s) Groundwater Encountered 1 23 ft 2 AN "X" IN SECTION BOX: **23** ft. 2 ft. 3 ft. OFFICE WELL'S STATIC WATER LEVEL 13.35 ft. below TOC measured on mo/day/yr 03/21/14 ŃW NE -Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter 8.25 in. to 26 ft. and in. to ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) W SW SE 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes _____ No X ___ If yes, mo/day/yr sample was Water Well Disinfected? Yes No X 5 TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped 3 RMP (SR) 1 Steel 6 Asbestos-Cement 9 Other (specify below) Welded 4 ABS Threaded Flush 7 Fiberglass -----Blank casing diameter 2 in. to 11 ft., Dia in. to ft., Dia in. to Casing height above land surface 0 in., weight 0.703 lbs./ft. Wall thickness or gauge No. SCH. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 9 ABS 12 None used (open hole) 2 Brass 4 Galvanized steel 6 Concrete tile SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 3 Mill slot 1 Continuous slot 6 Wire wrapped 9 Drilled holes 10 Other (specify) 2 Louvered shutter 4 Key punched 7 Torch cut SCREEN-PERFORATED INTERVALS: From 11 ft. to 21 ft. From ft. to ft.
 From
 ft. to
 ft. From
 ft. to
 ft. ft.

 From
 9
 ft. to
 26
 ft. From
 ft. to
 ft.
 GRAVEL PACK INTERVALS: ft. to From ft. From ft. to 6 GROUT MATERIAL: 2 Cement grout 3 Bentonite 4 Other 1 Neat cement Grout Intervals From 1 ft. to 9 ft. From ft. to ft. From ft. to ft.

What is	the nearest sour	ce of poss	ible cont	amination:				10	Lives	stock pens	14	Abandoned w	ater well	
1	Septic tank		4	Lateral lines	7	Pit privy		11	Fuel	storage	15	Oil well/ Gas v	well	
2 Sewer lines				Cess pool	8	Sewage la	igoon	12	Fertilizer storage		16	Other (specify	below)	
3 Watertight sewer lines								13 Insecticide storage						
Direction			How	many	y feet?									
FROM	/ TO	CODE		LITHOLOG	IC LOG		FROM	T	o	F	PLUGGING INTERVALS			
0	1			Topsoil, Silty Clay										
			Silty	ty Clay, dark brown to brown, tra		wn, trace	e							
1	24			ne fine sand										
24	25			y Clay										
25	26		Claye	y Sand										
		ļ												
										Survey Dat				
										Northing: 1	65847 ₄	4.43		
										Easting: 22	<u> 55975.</u>	.39		
		<u>.</u>												
7 CON	ITRACTOR'S OF	NODINAL S	VNER'S	CERTIFICATION:	This water	er well was	(1) construct	ed , (2	2) rec	onstructed, or (3)	plugged (under my jurisd	iction and was	
completed on (mo/day/yr) 03/20/14								s reco	ord is	true to the best o	f my knov	wledge and be	lief. Kansas	
Water V	Vell Contractor's	License N	D.	531			This Water Well Record was completed on (mo/day/yr) 04/14/14							
under th	.LC	by (signature)												
IN: Jak	STRUCTIONS: Pokson St., Ste. 420	ease fill in I , Topeka, K	olanks an Cansas 66	nd circle the correct a 3612-1367. Telepho	answers. Sone: 913-29	end three co	pies to Kansa nd one to WA	s Dep	artme VELL	ent of Health and E OWNER and retai	nvironmen	nt, Bureau of Wa	ter, 1000 S W	

贸