


1 LOCATION OF WATER WELL: County: <u>Butler</u>		Fraction <u>NE 1/4 NE 1/4 SW 1/4</u>	Section Number <u>14</u>	Township Number T <u>28</u> S	Range Number R <u>3</u> <u>EW</u>
Distance and direction from nearest town or city street address of well if located within city? <u>1 1/2 mi 4 E 1/4 N Rose Hill</u>					
2 WATER WELL OWNER: <u>Don Grunden</u> RR#, St. Address, Box #: <u>4318 Over</u> City, State, ZIP Code: <u>Wichita, KS 67216</u> Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: <u>140'</u> ft. ELEVATION: Depth(s) Groundwater Encountered 1. <u>120</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>100</u> ft. below land surface measured on mo/day/yr <u>6/27/95</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield <u>40</u> gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter <u>10</u> in. to ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well ① Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes <u>No</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>No</u>			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: <u>Glued</u> Clamped <u>PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter <u>5</u> in. to <u>120</u> ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface <u>12</u> in. weight <u>160</u> lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: <u>PVC</u> 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot ③ Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From <u>120</u> ft. to <u>140</u> ft. From ft. to ft. GRAVEL PACK INTERVALS: From <u>20</u> ft. to <u>140</u> ft. From ft. to ft. From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout ③ Bentonite 4 Other Grout Intervals: From <u>3</u> ft. to <u>20</u> ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool ⑧ Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? <u>E</u> How many feet? <u>50 +</u>					
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS			
0	5	Earth			
5	9	brown clay			
9	20	brownish yellow clay			
20	60	yellow clay			
60	140	shaley lime			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ① constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>6/27/95</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>493</u> This Water Well Record was completed on (mo/day/yr) <u>6/27/95</u> under the business name of <u>Rebecca Well Drilling</u> by (signature) <u>Rebecca Well Drilling</u>					