

1 LOCATION OF WATER WELL: County: <u>Butler</u>	Fraction <u>SW 1/4 NE 1/4 NE 1/4</u>	Section Number <u>17</u>	Township Number <u>T 28 S</u>	Range Number <u>R 3 EW</u>
--	---	-----------------------------	----------------------------------	-------------------------------

Distance and direction from nearest town or city street address of well if located within city?

2 N 1/2 E Rose Hill

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code	<u>Daryl R. Fitch</u> <u>RR#3 Box 189F</u> <u>Augusta, KS 67010</u>	Board of Agriculture, Division of Water Resources Application Number:
---	---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>95</u> ft. ELEVATION:
--	---

1 Mile

Depth(s) Groundwater Encountered 1 85 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 60 ft. below land surface measured on mo/day/yr 6/24/95

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 35 gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 10 in. to 9.5 ft., and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
① Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		10 Monitoring well

12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No NO

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
------------------------------	----------------	-----------------	---

1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded
② PVC	4 ABS	7 Fiberglass		Threaded

Blank casing diameter 5 in. to 7.5 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 12 in., weight lbs./ft. Wall thickness or gauge No. 540

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	③ Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 75 ft. to 95 ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 25 ft. to 75 ft., From ft. to ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	③ Bentonite	4 Other
-------------------	---------------	----------------	-------------	---------

GROUT INTERVALS: From 3 ft. to 25 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	<u>Open 20 Acres Field</u>

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	Earth			
4	8	Green clay			
8	50	Red clay			
50	60	Brownish red clay			
60	95	Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>6/24/95</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>993</u> This Water Well Record was completed on (mo/day/yr) <u>6/24/95</u> under the business name of <u>Reisner Well Drilling</u> by (signature) <u>Daryl R. Fitch</u>
