


1 LOCATION OF WATER WELL:		FRACTION			Water Well Record Form WWC-3 KSA 87-1212		
Butler		SW 1/4	SW 1/4	SW 1/4	4	T 28 S	R 3E E/W
Distance and direction from nearest town or city street address of well if located within city?							
14938 SW 130th      Augusta, Kansas							
WATER WELL OWNER: NOYSE, Dennis				Board of Agriculture, Division of Water Resource			
RR#, ST. ADDRESS, BOX #: 14938 SW 130th				Application Number:			
CITY, STATE, ZIP CODE: Augusta, Kansas							
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 112 ft. ELEVATION:		ft. 2		ft. 3	
		Depth(s) groundwater Encountered 1		ft. after		ft. hours pumping	
		WELL'S STATIC WATER LEVEL 15 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr				10/01/1996	
		Pump test data: Well water was		ft. after		gpm	
Est. Yield		gpm: Well water was		ft. after		gpm	
Bore Hole Diameter 12 in.		to 112 ft. and		in. to		ft.	
WELL WATER TO BE USED AS:		5 Public water supply		8 Air conditioning		11 Injection well	
1 Domestic		3 Feedlot		6 Oil field water supply		9 Dewatering	
2 Irrigation		4 Industrial		7 Lawn and garden only		12 Other (Specify below)	
Was a chemical/bacteriological sample submitted to Department? Yes		No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was		Water Well Disinfected? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>			
submitted							
5 TYPE OF CASING USED:							
1 Steel		3 RMP (SR)		5 Wrought iron		CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped	
2 PVC		4 ABS		6 Asbestos-Cement		Welded	
Blank casing Diameter 5 in. to 24		ft., Dia		7 Fiberglass		Threaded	
Casing height above land surface 12 in.,		weight 2.35		SDR-26			
6 TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel		3 Stainless Steel		5 Fiberglass		Wall thickness or gauge No. 10 Asbestos-cement	
2 Brass		4 Galvanized steel		6 Concrete tile		.214	
7 ABS		8 PVC		9 ABS		11 other (specify)	
SCREEN OR PERFORATION OPENING ARE:		5 Gauzed wrapped		8 Saw cut		12 None used (open hole)	
1 Continous slot		6 Wire wrapped		9 Drilled holes		13 Insecticide storage	
2 Louvered shutter		7 Torch cut		10 Other (specify)		14 Abandon water well	
SCREEN-PERFORATION INTERVALS: from 24 ft. to 112 ft. From ft. to ft.							
GRAVEL PACK INTERVALS: from 24 ft. to 112 ft. From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other <b>bentonite hole plug</b>							
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to ft.							
What is the nearest source of possible contamination:							
1 Septic tank		4 Lateral lines		7 Pit privy		10 Livestock pens	
2 Sewer lines		5 Cess pool		8 Sewage lagoon		11 Fuel storage	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		12 Fertilizer storage	
						13 Insecticide storage	
7 How many feet? <b>None Apparent</b>							
FROM TO LITHOLOGIC LOG			FROM TO			PLUGGING INTERVALS	
0	4	topsoil					
4	18	clay					
18	112	shale					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <b>10/01/1996</b> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <b>236</b> This Water Well Record was completed on (mo/day/yr) <b>10/02/96</b> .							
Under the business name of <b>Harp Well &amp; Pump Service, Inc.</b> by (signature) <i>Todd S. Harp</i>							