

1) LOCATION OF WATER WELL: County: Butler Fraction: NE 1/4 NW 1/4 NW 1/4 Section Number: 31 Township Number: T 28 S Range Number: R 3 E

Distance and direction from nearest town or city street address of well if located within city? IN City of Rose Hill

2) WATER WELL OWNER: Darryle Dasher Rose Hill

RR#, St. Address, Box # 912 McCaskey 67133 Board of Agriculture, Division of Water Resources

City, State, ZIP Code 912 McCaskey 67133 Application Number:

3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4) DEPTH OF COMPLETED WELL: 95 ft. ELEVATION: 40 ft.

Depth(s) Groundwater Encountered 1. 40 ft. 2. 40 ft. 3. 40 ft.

WELL'S STATIC WATER LEVEL 30 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 40 ft. after 40 hours pumping 40 gpm

Est. Yield 40 gpm Well water was 40 ft. after 40 hours pumping 40 gpm

Bore Hole Diameter 9 1/2 in. to 9 1/2 in. and 9 1/2 in. to 9 1/2 in.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes X No X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No X

5) TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)

2 PVC 4 ABS 7 Fiberglass

Blank casing diameter 5 in. to 60 ft. Dia. 5 in. to 60 ft. Dia. 5 in. to 60 ft. Dia. 5 in. to 60 ft. Dia.

Casing height above land surface 18 in., weight 160 lbs./ft. Wall thickness or gauge No. 214

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes

2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 60 ft. to 95 ft. From 60 ft. to 95 ft. From 60 ft. to 95 ft. From 60 ft. to 95 ft.

GRAVEL PACK INTERVALS: From 40 ft. to 95 ft. From 40 ft. to 95 ft. From 40 ft. to 95 ft. From 40 ft. to 95 ft.

6) GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 23 ft. From 3 ft. to 23 ft. From 3 ft. to 23 ft. From 3 ft. to 23 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage

Direction from well? S How many feet? 50

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 3 Soil 0 3

3 18 clay 3 18

18 95 shale + lime 18 95

7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/10/00 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 251 This Water Well Record was completed on (mo/day/yr) 5/8/00

under the business name of Winter Well Drilling by (signature) Charles Winter

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.