


1 LOCATION OF WATER WELL:	Fraction $\frac{1}{4}$ C NW $\frac{1}{4}$ NW $\frac{1}{4}$	Section Number 32	Township Number T 28 S	Range Number R 3E EW
County: Butler				

Distance and direction from nearest town or city street address of well if located within city?

1017 Park Rd, Rose Hill, KS

2 WATER WELL OWNER: Greg Jones	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: 214 N. Chestnut	Application Number:
City, State, ZIP Code: Douglas, KS 67039	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	DEPTH OF COMPLETED WELL: 80' ft. ELEVATION:
	Depth(s) Groundwater Encountered 1 28 ft. 2 ft. 3 ft.
	WELL'S STATIC WATER LEVEL 28 ft. below land surface measured on mo/day/yr 10-16-01
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 9 in. to 80 ft. and in. to ft.
	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
	Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 5 in. to 60 ft. Dia			11 Other (specify)
Casing height above land surface 12 in. weight lbs./ft. Wall thickness or gauge No. 5.2 R26			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	1 Continuous slot	3 Mill slot	4 Key punched
SCREEN-PERFORATED INTERVALS:	From 60 ft. to 80 ft.	From ft. to ft.	From ft. to ft.
GRAVEL PACK INTERVALS:	From 20 ft. to 80 ft.	From ft. to ft.	From ft. to ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:	From 4 ft. to 20 ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)
Direction from well?				How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	18	clay			
18	35	shale			
35	37	lime			
37	48	shale			
48	58	lime + shale			
58	75	shale			
75	80	lime			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-16-01 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 171 This Water Well Record was completed on (mo/day/yr) 11-10-01 under the business name of G & S Drilling Inc. by (signature) [Signature]
