

1 LOCATION OF WATER WELL: County: <u>Butler</u>	Fraction <u>NW 1/4 SW 1/4 NW 1/4</u>	Section Number <u>5</u>	Township Number <u>28</u> S	Range Number <u>3</u> E
--	--------------------------------------	-------------------------	-----------------------------	-------------------------

Distance and direction from nearest town or city street address of well if located within city?
2 1/4 Miles South of 400 Hwy on Southeast Butler Rd 1/4 Mile east

2 WATER WELL OWNER: <u>J. J. Infell</u> RR#, St. Address, Box # : <u>Pine Meadow of Anderson, KS 67002</u> City, State, ZIP Code : <u>Anderson, KS 67002</u>	Board of Agriculture, Division of Water Resources Application Number:
--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL <u>60</u> ft. ELEVATION:
--	--

Depth(s) Groundwater Encountered 1 28 ft. 2 ft. 3 ft.

WELL'S STATIC WATER LEVEL 28 ft. below land surface measured on mo/day/yr 6-21-02

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 25 gpm: Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No ✓; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes ✓ No

5 TYPE OF BLANK CASING USED: 1 Steel <u>2 PVC</u> 3 RMP (SR) 4 ABS	5 Wrought iron 6 Asbestos-Cement 7 Fiberglass	8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued <u>✓</u> Clamped Welded Threaded
--	---	---

Blank casing diameter 5 in. to 40 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 12 in., weight SDR 26 lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC

1 Steel 2 Brass	3 Stainless Steel 4 Galvanized Steel	5 Fiberglass 6 Concrete tile
--------------------	---	---------------------------------

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 2 Louvered shutter	3 <u>Mill slot</u> 4 Key punched	5 Gauzed wrapped 6 Wire wrapped 7 Torch cut
---	-------------------------------------	---

SCREEN-PERFORATED INTERVALS: From 40 ft. to 60 ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 23 ft. to 60 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement	2 Cement grout	3 <u>Bentonite</u>
---------------------------------	----------------	--------------------

Grout Intervals: From 0 ft. to 23 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank 2 Sewer lines <u>3 Watertight sewer lines</u>	4 Lateral lines 5 Cess pool 6 Seepage pit	7 Pit privy 8 Sewage lagoon 9 Feedyard
---	---	--

Direction from well? West

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>2</u>	<u>Top Soil</u>			
<u>2</u>	<u>18</u>	<u>Brown Clay</u>			
<u>18</u>	<u>28</u>	<u>Gray shale</u>			
<u>28</u>	<u>60</u>	<u>lime / Broken / shale streaks</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1)</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>6-21-02</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No <u>464</u> This Water Well Record was completed on (mo/day/yr) <u>6-28-02</u> under the business name of <u>Water Well Services</u> by (signature) <u>Robert J. Sharp</u>
--