

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: BUTLER		NW 1/4 SW 1/4 SW 1/4	21	T 28 S	R 3 E
Distance and direction from nearest town or city street address of well if located within city? 1 mi EAST AND 3/4 NORTH of Rose Hill					
2 WATER WELL OWNER: LOUIS A. CLAASSEN		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #: 15009 TIMBER LAKE CIRCLE		Application Number:			
City, State, ZIP Code: WICHITA, KS. 67230					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 45 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr 3/6/92			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 60 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 10 in. to ft., and in. to ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well ☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes ☒ No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR) ☒ 2 PVC 4 ABS		5 Wrought iron 8 Concrete tile Welded 6 Asbestos-Cement 9 Other (specify below) Threaded			
Blank casing diameter 5 in. to ft., Dia 160 in. to ft., Dia		Casing height above land surface 12 in., weight 160 lbs./ft. Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL:		☒ 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot ☒ 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		From 40 ft. to 60 ft., From ft. to ft. From ft. to ft., From ft. to ft.			
GRAVEL PACK INTERVALS:		From 20 ft. to 40 ft., From ft. to ft. From ft. to ft., From ft. to ft.			
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout ☒ 3 Bentonite 4 Other			
Grout Intervals: From 3 ft. to 20 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool ☒ 6 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage			
Direction from well? down slope		How many feet? 70+			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
6	4	earth (green) shale (gray) shale (pink)			
4	12				
12	40				
40	60				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/6/92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 493 This Water Well Record was completed on (mo/day/yr) under the business name of Rebecca's Well Drilling by (signature) <i>Rebecca's Well Drilling</i>					