	WATER WE	LL RECORD	Form vv v		SA 82a-121			
1 LOCATION OF WATER WELL:	FRACTION	OP C		TION NUMBER			RANGE NO	
Butler	SW 1/4	SE 1/4 S	E 1/4	31	⊤ 28	S	R 3E	E/W
Distance and direction from nearest town or city	street address of well if	located within city?						
231 Sunrise Ct.	Rosehill, Kans	as						
2 WATER WELL OWNER: HAT	J GH, Jeffrey							
RR#,ST. ADDRESS,BOX #: 231	Sunrise Ct.					Board of Agn	iculture, Division of W	Vater Resource
CITY, STATE: Rose	ehill, Kansas		ZI	IP CODE:		Application Nur	nber:	
	DEPTH OF COMPL	ETED WELL:	110 ft.		ELEVATION:			
WITH AN "X" IN SECTION BOX:						ft.		ft.
1 -	epth of groundwater E		ft					
]	'ELL'S STATIC WAT	ER LEVEL 28	FT. BELC	W LAND S!	IRFACE MEASU	RED ON mo/o	day/yr: 11/2	2/16
NW	Pum	o test data: Well	water was		ft. after	hours	s of pumping @	gpm
<u> 0 </u>	Est. Yield:	gpm Wel	l water was		ft. after	hours	s of pumping @	gpm
₩ ₩ E E	Bore Hole Diameter	12 in.	to 1	110 ft.	and	in.	to	ft.
	ELL WATER TO BE	USED AS:				9. Dewateri	ng 11. Injed	ction well
sw se	1. Domestic 3. F	eedlot 5. Public	water supply	7. Lawn a	nd garden only			pecify below)
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well								
S	Was a chemical/bacterio	logical sample submitted	to Department?	YES	NO		what mo/day/yr v	
St	ubmitted			Was V	Vater Well Disinfo	ected?	YES I	<u> 10</u>
5 TYPE OF CASING USED:	5. Wrought Ir	on 7. Fibergl	ass 9. O	ther (Specify	below) CAS	ING JOINTS:	Glued	Threaded
1. Steel 3. RPM (S	R)	•	SD.	R-26			Welded	Clamped
2. PVC 4. ABS	6. Asbestos-	Cement 8. Concre	ete tile 3D	120				
Blank casing diameter 5	in. to 4	0 ft., Dia.	in.	to	ft., [Dia.	in. to	ft.
Casing height above land surface:	12 in.,	Weight:	2.35	bs. / ft.	Wall thi	ckness or gain	ge No214	
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214 TYPE OF SCREEN OR PERFORATION MATERIAL:								
	5. Fiberglass	7. PVC	9. A	RS	11. Oth	er (specify)		
	-					, , , ,	hata\	
2. Brass 4. Galvanized	6. Concrete Tile	e 8. RMP (S	10. A	Asbestos-Cen	nent 12. No	ne used (open	noie)	
SCREEN OR PERFORATION OPENIN	GS ARE:							
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open h						pen hole)		
2. Louvered shutter 4. Key p	ounched 6. W	ire wrapped	(8 Sa	w cut	10. Othe	er (specify)		
2. Louveled shaker 4. Key p	o. v.	• • •	_		10. 01	(0,00)		
SCREEN - PERFORATION INTERVAL	From	40 ft.	to 110	ft.,	From	ft.	to	ft.
	From	ft.	to	ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS:	From	24 ft.	to 110	ft.,	From	ft.	to	ft.
1	-	ft.	to		5			
	From	π,	10	ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug							ug	
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.								ft.
What is the nearest source of possible of		Dit mains	10 Liveston	k none	12 Inconti	aida atarana	15 Oil wall	Sae well
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well								
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)								
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage								
Direction from well? South					How ma	ny feet? 20	ft. plus	
From To	LITHOLOGIC	LOG	From	То			OGÍC LOG	
0 3 topsoil			1.10				, , , , , , , , , , , , , , , , , , , ,	
3 20 clay				1				
20 90 grey shale								
90 105 red shale								
105 110 limestone								
TO THE IMPESIONE				1				
				†				
7			\prec					U
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and								
was completed on (mo/day/year) 11/02/2016 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's Licer	nse No. 236	This water	er well record wa	as completed	on (mo/dav/vea	r) 11/A	7/2016	
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp								