WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Butler NE 1/4 NE 1/4 1/4 31 Т 28 S 3E R E/W Distance and direction from nearest town or city street address of well if located within city? 1360 N. Country Homes Inc. Rosehill, Kansas LEEWOOD HOMES INC. WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 3500 N. Rock Road, Bldg. 2200 #204 Wichita, Kansas CITY, STATE: ZIP CODE Application Number: 90 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: ELEVATION: WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. ft. WELL'S STATIC WATER LEVEL 36 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 2/24/17 Well water was NW Pump test data: ft. after ŊΕ apri Est. Yield: gpm Well water was ft. after hours of pumping @ apm 12 ≌ Bore Hole Diameter ft WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 3. Feedlot 1. Domestic 12. Other (Specify below) 8. Air conditioning 10. Monitoring well 2. Irrigation 4. Industrial 6. Oil field water supply ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) submitted Was Water Well Disinfected? (YES) TYPE OF CASING USED: 5 CASING JOINTS: Glued 9. Other (Specify below) Threaded 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS Blank casing diameter to 45 Dia. in. ft., ft.. Dia to in to ft. 12 Casing height above land surface: 2.35 in., Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 1. Steel 3. Stainless Steel 5. Fiberglass 9. ABS 11. Other (specify) 2. Brass Concrete Tile 8. RMP (SR) 12. None used (open hole) 4 Galvanized Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous stot 3. Mill slot 7. Torch cut 9. Drilled holes 5. Gauzed wrapped 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 45 90 From to ft., From ft. ft. to ft., From ft. **GRAVEL PACK INTERVALS:** 24 ft to 90 From ft., From ft. ft. From to ft.. From ft. **GROUT MATERIALS:** Other 6 1. Neat cement 2. Cement Grout 3. Bentonite bentonite hole plug Grout Intervals: From 4 24 ft., From ft. to ft., From What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 4. Lateral lines 1. Septic tank 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 2. Sewer lines 5. Cess Pool 9. Feed yard 12. Fertilizer storage 6. Seepage pit 3 Watertight sewer line How many feet? 10 ft. plus Direction from well? From Τo LITHOLOGIC LOG From. To LITHOLOGIC LOG topsoil 14 clay 14 brown shale 35 gray shale Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and 2/24/17 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year)

by (signature)

Todd S. Harb

under the business name of Harp Well and Pump Service