WATER	WELL I	RECORD Form	WWC-5		vision of Water				
Origina	l Record	Correction Chan	ge in Well Use	Re	sources App. No	о	Well ID		
1 LOCA	TION OF W	VATER WELL:	Fraction	Se	ection Number	Township Numl			
Count	y: Butler		SE 1/4 SW 1/4 SW 1/4	1/4 1/4 5 T 28 S R 3 ■ E 🗆 W					
2 WELL OWNER: Last Name: First: Street or Rural Address where well is located (if unknown, distance and									
	Nies Hon		THSt.	direction from nearest town or intersection): If at owner's address, check here:					
Address: 10333 F 21ct ST N #303							_		
Address: 417 S. Prairie Point, Andover, KS 67002									
City:	Wichita	State: KS	ZIP: 67206	20 Maria 1997 - 20 Maria		NOW C. AND CO.			
3 LOCAT		A DEPOSIT OF CO.	ADV MINES AND A	05	6				
WITH "			MPLETED WELL:						
SECTIO	ON BOX:		Encountered: 1)						
1	N		3) ft., or 4)				34 □ NAD 83 □ NAD 27		
l ——			ATER LEVEL:			for Latitude/Longitude			
}   '	'		e, measured on (mo-day						
NW	NE		e, measured on (mo-day		I	(WAAS enabled?			
	Pump test data: Well water was  Well water was after hours pumping								
W	E								
sw	SE		water was						
X		Estimated Viold	rs pumping	. gpm	6 Elevat	ion: f	t. Ground Level TOC		
	S	Estimated Yield:	10" in to 85	ft and			GPS Topographic Map		
1	mile	Boie Hole Diameter: .					O.O. T. toboBraham and		
7 WELL WATER TO BE USED AS:									
1. Domestic			ater Supply: well ID			Field Water Supply:	lease		
House				my wells? 11. Test Hole: wel					
	& Garden						☐ Cased ☐ Uncased ☐ Geotechnical		
Livest			ng: well ID						
2. Irrigat			tal Remediation: well I						
3. Feedle		Air Sparg		Extraction			ischarge Inj. of Water		
4. 🔲 Indust	rial	☐ Recovery	☐ Injection						
Was a chemical/bacteriological sample submitted to KDHE?  Yes No If yes, date sample was submitted:									
Water well	disinfected'	? 🔲 Yes 🔳 No				•			
8 TYPE (	OF CASING	USED: Steel P	/C □ Other	CAS	ING JOINTS:	■ Glued □ Clampe	d D Welded D Threaded		
8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 5" in to 85 ft Diameter in to ft Diameter in to ft									
Casing diameter									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
☐ Steel ☐ Stainless Steel ☐ Fiberglass ■ PVC ☐ Other (Specify)									
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
☐ Continuous Slot									
Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole)									
SCREEN-PERFORATED INTERVALS: From .65 ft., to .85 ft., From ft., From ft., From ft.									
GRAVEL PACK INTERVALS: From 22' ft. to 85 ft., From ft. to ft., From ft. to ft.									
OCHOLIE FACE INTERVALS. From 22. II. to 99. II., From II. to II., From III. to II.									
9 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☐ Bentonite ☐ Other  Grout Intervals: From									
Grout Interv	als: From		It., From	. It. to	H., From .	ft. to	II.		
Nearest source of possible contamination:									
Septic		☐ Lateral Lin☐ Cess Pool	_ :		Livestock Pen		icide Storage		
Other	(Specify)	ines	t ☐ Feedyard	L	Fertilizer Stor	age 🔲 Oil W	ell/Gas Well		
☐ Other (Specify) Direction from well? SW Distance from well? 50+									
10 FROM	TO	LUTIOLO	Distance from w						
0		LITHOLO	GIC LUG	FROM	10	LITHU. LUG (cont.) o	or PLUGGING INTERVALS		
		dirt							
2	7	clay		<u> </u>	1				
56	85	shaley lime							
				Notes:					
	1								
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged									
under my inriediction and was completed on (mo-day year) 4/3/17									
under my jurisdiction and was completed on (mo-day-year) .4/3/17									
under the business name of Reiserer Well Drilling Signature Jarry Reiserer									
Mail 1 white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water, GWTS Section,									
1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524.									
		s.gov/waterwell/index.html		KSA 82a-1			Revised 7/10/2015		