KOLAR Document ID: 1582610

Original Record Correction Change in Well Use Reso							Wall ID			
					rces App. N		Well ID	NT 1		
1 LOCATION OF V	WATER WELL:	Fraction		Section	on Numbe	1		ge Number		
County:		1/4 1/4 1/4	-			T S	R	$\square \to \square W$		
2 WELL OWNER:	First:	Street or Rural Address where well is located (
Business:			direction fr	om nea	arest town or	intersection): If at owner's	address, c	heck here:		
Address:										
Address:	C4-4-:	ZID.								
City:	State:	ZIP:								
3 LOCATE WELL	4 DEPTH OF COM	IPLETED WELL:	5 Latitude:(decimal degrees)							
WITH "X" IN	Depth(s) Groundwater				Longitude:(decimal degrees)					
SECTION BOX:		3) ft., or 4)		1	Datum	: ☐ WGS 84 ☐ NAD	83 DN	ΔD 27		
WELL'S STATIC WATER LEVEL:						for Latitude/Longitude:	05 🗀 11	110 27		
	below land surface, measured on (mo-day-yr) above land surface, measured on (mo-day-yr) Pump test data: Well water was					PS (unit make/model:)		
NW NF					·· (WAAS enabled? ☐ Yes ☐ No) ☐ Land Survey ☐ Topographic Map					
'`' X'										
$ \mathbf{w} $	after hour	after hours pumping gpm				Online Mapper:				
	Well v	Well water was ft.								
SW SE	anter nours pumping									
	Estimated Yield:				6 Elevation:ft. Ground Level TOC					
S	in. to ft. and			Source:						
mile		in. to	ft.			☐ Other				
7 WELL WATER TO BE USED AS:										
1. Domestic:	5. ☐ Public Wε	ater Supply: well ID			10. □ Oil	Field Water Supply: leas	se			
☐ Household	6. ☐ Dewatering: how many wells?				. 11. Test Hole: well ID					
□ Lawn & Garden										
☐ Livestock	Livestock 8. Monitoring: well ID					12. Geothermal: how many bores?				
2. ☐ Irrigation	Irrigation 9. Environmental Remediation: well ID					a) Closed Loop				
3. ☐ Feedlot	3. ☐ Feedlot ☐ Air Sparge ☐ Soil Vapor Extraction					b) Open Loop Surface Discharge Inj. of Water				
4. ☐ Industrial	☐ Recovery	☐ Injection			13. 🔲 Otl	her (specify):				
Was a chemical/bacteriological sample submitted to KDHE? ☐ Yes ☐ No If yes, date sample was submitted:										
Water well disinfected? \square Yes \square No										
8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded										
Casing diameter										
Casing height above land surface in. Weight lbs./ft. Wall thickness or gauge No.										
TYPE OF SCREEN OR PERFORATION MATERIAL:										
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify) ☐ None yead (one) help)										
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)										
SCREEN OR PERFORATION OPENINGS ARE:										
☐ Continuous Slot ☐ Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify)										
☐ Louvered Shutter ☐ Key Punched ☐ Wire Wrapped ☐ Saw Cut ☐ None (Open Hole)										
SCREEN-PERFORATED INTERVALS: From										
GRAVEL PACK INTERVALS: From										
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other										
Grout Intervals: From										
Nearest source of possible contamination: No potential source of contamination within 200 ft.										
☐ Septic Tank ☐ Lateral Lines ☐ Pit Privy ☐ Livestock Pens ☐ Insecticide Storage										
☐ Sewer Lines ☐ Cess Pool ☐ Sewage Lagoon ☐ Fuel Storage ☐ Abandoned Water Well										
☐ Watertight Sewer Lines ☐ Seepage Pit ☐ Feedyard ☐ Fertilizer Storage ☐ Oil Well/Gas Well										
☐ Other (Specify)										
							HICCIN	CINTEDMALC		
10 FROM TO	LITHOLO	GIC LUG	FRON	1	ТО	LITHO. LOG (cont.) or P	LUGGIN	JINIEKVALS		
										
			Notes:				_			
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged										
under my jurisdiction and was completed on (mo-day-year)										
Kansas Water Well Co	ontractor's License No	This W	ater Well	Recoi	rd was con	npleted on (mo-day-vea	r)			
under the business name of										
Send one copy to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.										
KS Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-3565.										
Visit us at http://www.kdheks.gov/waterwell/index.html KSA 82a-1212										