

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction SE $\frac{1}{4}$ SW $\frac{1}{4}$ NW $\frac{1}{4}$	Section Number 3	Township Number T 28 S	Range Number R 3E <input checked="" type="radio"/>
Distance and direction from nearest town or city street address of well if located within city? 31 St. So. 2 miles East of Rosehill Rd., $\frac{1}{2}$ So., $\frac{1}{4}$ East ..Northside					
2 WATER WELL OWNER:		Jim Reynolds Rt. #3 Box 172A Augusta, Ks. 67010		Board of Agriculture, Division of Water Resources Application Number: 733-0556	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		<input checked="" type="checkbox"/> 4 DEPTH OF COMPLETED WELL 126 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 21 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 21 ft. below land surface measured on mo/day/yr 6-9-88 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 11 in. to ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes <input checked="" type="checkbox"/> No	
5 TYPE OF BLANK CASING USED:		1 Steel 3 RMP (SR) 2 PVC 4 ABS	5 Wrought iron 8 Concrete tile 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass Cer-Mac styrene SDR-26	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped Welded Threaded	
Blank casing diameter 5 in. to 30 ft., Dia in. to ft., Dia in. to ft.		Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. 203			
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 2 Brass 4 Galvanized steel		5 Fiberglass 7 PVC 6 Concrete tile 8 RMP (SR) 9 ABS	10 Asbestos-cement 11 Other (specify) 12 None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 2 Louvered shutter 4 Key punched		5 Gauzed wrapped 8 Saw cut 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)	11 None (open hole)		
SCREEN-PERFORATED INTERVALS: From 30 ft. to 126 ft., From ft. to ft.					
From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 25 ft. to 126 ft., From ft. to ft.					
From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.	3 Bentonite 4 Other	How many feet? 250	
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pit		7 Pit privy 10 Livestock pens 8 Sewage lagoon 11 Fuel storage 9 Feedyard 12 Fertilizer storage 13 Insecticide storage	14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)		
Direction from well? East					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	topsoil			
3	11	clay			
11	126	grey shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-9-88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 5-15-89 under the business name of **Harp Well and Pump Service, Inc.** by (signature) *Mary Arnold*

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.