

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Butler	SW 1/4 SE 1/4 NE 1/4	5	T 28 S	R 3 E

Distance and direction from nearest town or city street address of well if located within city?

in City of Rose Hill

2 WATER WELL OWNER:	RR#, St. Address, Box #	City, State, ZIP Code	Board of Agriculture, Division of Water Resources
Darrel Williams	104 N. Bentwood	Rose Hill KS 67133	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL:	ELEVATION:
	80 ft.	73 ft.
	Depth(s) Groundwater Encountered 1. 73 ft. 2. 73 ft. 3. 73 ft.	
	WELL'S STATIC WATER LEVEL 14 ft. below land surface measured on mo/day/yr 3/18/93	
	Pump test data: Well water was 40 gpm. Well water was 40 gpm.	
	Est. Yield 40 gpm. Well water was 40 gpm.	
	Bore Hole Diameter 4 in. to 4 ft., and 4 in. to 4 ft.	
	WELL WATER TO BE USED AS:	
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
	2 Irrigation 4 Industrial 7 <u>Lawn and garden only</u> 10 Monitoring well	
	Was a chemical/bacteriological sample submitted to Department? Yes Yes No No If yes, mo/day/yr sample was submitted	
	Water Well Disinfected? Yes Yes No No	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded Threaded
Blank casing diameter 5 in. to 5 ft., Dia 5 in. to 5 ft., Dia 5 in. to 5 ft.			
Casing height above land surface 12 in., weight 160 lbs./ft. Wall thickness or gauge No. 160			
TYPE OF SCREEN OR PERFORATION MATERIAL:	PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Min slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 60 ft. to 80 ft., From 60 ft. to 80 ft., From 60 ft. to 80 ft.		
GRAVEL PACK INTERVALS:	From 20 ft. to 80 ft., From 20 ft. to 80 ft., From 20 ft. to 80 ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 3 ft. to 20 ft., From 3 ft. to 20 ft., From 3 ft. to 20 ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
Direction from well? West				13 Insecticide storage
				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)
				How many feet? 50+

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	earth			
4	36	brn clay			
36	58	yellow clay			
58	70	gray shale			
70	80	shaly lime			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/18/93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 493 This Water Well Record was completed on (mo/day/yr) 3/18/93 under the business name of Risser Well Drilling by (signature) Jerry Risser
--