


1 LOCATION OF WATER WELL: Fraction NE 1/4 SE 1/4 SW 1/4 Section Number 15 Township Number T 30 S Range Number R 3 E/W

Distance and direction from nearest town or city street address of well if located within city?
4 East 5 South of Wichita

2 WATER WELL OWNER: Allen Girkens
RR#, St. Address, Box # 3639 143 East 7 67214 Board of Agriculture, Division of Water Resources
City, State, ZIP Code 3639 143 East 7 67214 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 100 ft. ELEVATION: 85 ft.
Depth(s) Groundwater Encountered 1. 85 ft. 2. 60 ft. 3. 60 ft.
WELL'S STATIC WATER LEVEL 60 ft. below land surface measured on mo/day/yr
Pump test data: Well water was 20 ft. after 20 hours pumping 20 gpm
Est. Yield 20 gpm: Well water was 20 ft. after 20 hours pumping 20 gpm
Bore Hole Diameter 20 in. to 20 ft. and 20 in. to 20 ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
① Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
1 Steel ③ RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
2 PVC 4 ABS 7 Fiberglass Threaded
Blank casing diameter 5 in. to 100 ft. Dia. 5 in. to 100 ft. Dia. 5 in. to 100 ft. Dia. 5 in. to 100 ft. Dia.
Casing height above land surface 18 in. weight 200 lbs./ft. Wall thickness or gauge No. 12.14
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass ⑧ RMP (SR) 11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped ⑧ Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 60 ft. to 100 ft. From 60 ft. to 100 ft. From 60 ft. to 100 ft. From 60 ft. to 100 ft.
GRAVEL PACK INTERVALS: From 40 ft. to 100 ft. From 40 ft. to 100 ft. From 40 ft. to 100 ft. From 40 ft. to 100 ft.

6 GROUT MATERIAL: 1 Neat cement ② Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 13 ft. From 0 ft. to 13 ft. From 0 ft. to 13 ft. From 0 ft. to 13 ft.
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool ⑧ Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
Direction from well? N W How many feet? 200

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	Soil			
3	6	Clay			
6	15	Clay & Rock			
15	25	Rock			
25	45	Shale			
45	100	Lime & Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/26/82 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 1251 This Water Well Record was completed on (mo/day/year) 12/26/82 under the business name of Winter Well Drilling by (signature) Charles Winter

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.