

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: BUTLER	NE ¼ NW ¼ NW ¼	16	T 28 S	R 3 EW

Distance and direction from nearest town or city street address of well if located within city?

~~1 1/2 East of Rosehill Rd south side of McArthur Rosehill, Ks.~~

2. WATER WELL OWNER:	Steve Korte	
RR#, St. Address, Box # :	Rt #3	Board of Agriculture, Division of Water Resources
City, State, ZIP Code :	Augusta, Kansas	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL... 7.2 ... ft. ELEVATION: ...

Depth(s) Groundwater Encountered 1. 25 ft. 2. 25 ft. 3. 25 ft.
 WELL'S STATIC WATER LEVEL 25 ft. below land surface measured on mo/day/yr 9-5-84
 Pump test data: Well water was _____ ft. after _____ hours pumping _____ gpm
 Est. Yield _____ gpm: Well water was _____ ft. after _____ hours pumping _____ gpm
 Bore Hole Diameter 1.1 in. to _____ ft., and _____ in. to _____ ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) _____
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well _____
 Was a chemical/bacteriological sample submitted to Department? Yes _____ No X; If yes, mo/day/yr sample was sub-
 mitted _____
 Water Well Disinfected? Yes X No _____

5 TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued .. X .. Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC	4 ABS ==	7 Fiberglass	Cer-Mac styrene SDR-26	Threaded

Blank casing diameter 5 in. to 32 ft. Dia. 32 in. to 48 in. Dia. 48 in. to 60 in. Dia. 60 in. to 72 in. Dia. 72 in. to 84 in. Dia. 84 in. to 96 in. Dia. 96 in. to 108 in. Dia. 108 in. to 120 in. Dia. 120 in. to 144 in. Dia. 144 in. to 168 in. Dia. 168 in. to 192 in. Dia. 192 in. to 216 in. Dia. 216 in. to 240 in. Dia. 240 in. to 264 in. Dia. 264 in. to 288 in. Dia. 288 in. to 312 in. Dia. 312 in. to 336 in. Dia. 336 in. to 360 in. Dia. 360 in. to 384 in. Dia. 384 in. to 408 in. Dia. 408 in. to 432 in. Dia. 432 in. to 456 in. Dia. 456 in. to 480 in. Dia. 480 in. to 504 in. Dia. 504 in. to 528 in. Dia. 528 in. to 552 in. Dia. 552 in. to 576 in. Dia. 576 in. to 600 in. Dia. 600 in. to 624 in. Dia. 624 in. to 648 in. Dia. 648 in. to 672 in. Dia. 672 in. to 696 in. Dia. 696 in. to 720 in. Dia. 720 in. to 744 in. Dia. 744 in. to 768 in. Dia. 768 in. to 792 in. Dia. 792 in. to 816 in. Dia. 816 in. to 840 in. Dia. 840 in. to 864 in. Dia. 864 in. to 888 in. Dia. 888 in. to 912 in. Dia. 912 in. to 936 in. Dia. 936 in. to 960 in. Dia. 960 in. to 984 in. Dia. 984 in. to 1008 in. Dia. 1008 in. to 1032 in. Dia. 1032 in. to 1056 in. Dia. 1056 in. to 1080 in. Dia. 1080 in. to 1104 in. Dia. 1104 in. to 1128 in. Dia. 1128 in. to 1152 in. Dia. 1152 in. to 1176 in. Dia. 1176 in. to 1200 in. Dia. 1200 in. to 1224 in. Dia. 1224 in. to 1248 in. Dia. 1248 in. to 1272 in. Dia. 1272 in. to 1296 in. Dia. 1296 in. to 1320 in. Dia. 1320 in. to 1344 in. Dia. 1344 in. to 1368 in. Dia. 1368 in. to 1392 in. Dia. 1392 in. to 1416 in. Dia. 1416 in. to 1440 in. Dia. 1440 in. to 1464 in. Dia. 1464 in. to 1488 in. Dia. 1488 in. to 1512 in. Dia. 1512 in. to 1536 in. Dia. 1536 in. to 1560 in. Dia. 1560 in. to 1584 in. Dia. 1584 in. to 1608 in. Dia. 1608 in. to 1632 in. Dia. 1632 in. to 1656 in. Dia. 1656 in. to 1680 in. Dia. 1680 in. to 1704 in. Dia. 1704 in. to 1728 in. Dia. 1728 in. to 1752 in. Dia. 1752 in. to 1776 in. Dia. 1776 in. to 1800 in. Dia. 1800 in. to 1824 in. Dia. 1824 in. to 1848 in. Dia. 1848 in. to 1872 in. Dia. 1872 in. to 1896 in. Dia. 1896 in. to 1920 in. Dia. 1920 in. to 1944 in. Dia. 1944 in. to 1968 in. Dia. 1968 in. to 1992 in. Dia. 1992 in. to 2016 in. Dia. 2016 in. to 2040 in. Dia. 2040 in. to 2064 in. Dia. 2064 in. to 2088 in. Dia. 2088 in. to 2112 in. Dia. 2112 in. to 2136 in. Dia. 2136 in. to 2160 in. Dia. 2160 in. to 2184 in. Dia. 2184 in. to 2208 in. Dia. 2208 in. to 2232 in. Dia. 2232 in. to 2256 in. Dia. 2256 in. to 2280 in. Dia. 2280 in. to 2304 in. Dia. 2304 in. to 2328 in. Dia. 2328 in. to 2352 in. Dia. 2352 in. to 2376 in. Dia. 2376 in. to 2400 in. Dia. 2400 in. to 2424 in. Dia. 2424 in. to 2448 in. Dia. 2448 in. to 2472 in. Dia. 2472 in. to 2496 in. Dia. 2496 in. to 2520 in. Dia. 2520 in. to 2544 in. Dia. 2544 in. to 2568 in. Dia. 2568 in. to 2592 in. Dia. 2592 in. to 2616 in. Dia. 2616 in. to 2640 in. Dia. 2640 in. to 2664 in. Dia. 2664 in. to 2688 in. Dia. 2688 in. to 2712 in. Dia. 2712 in. to 2736 in. Dia. 2736 in. to 2760 in. Dia. 2760 in. to 2784 in. Dia. 2784 in. to 2808 in. Dia. 2808 in. to 2832 in. Dia. 2832 in. to 2856 in. Dia. 2856 in. to 2880 in. Dia. 2880 in. to 2904 in. Dia. 2904 in. to 2928 in. Dia. 2928 in. to 2952 in. Dia. 2952 in. to 2976 in. Dia. 2976 in. to 3000 in. Dia. 3000 in. to 3024 in. Dia. 3024 in. to 3048 in. Dia. 3048 in. to 3072 in. Dia. 3072 in. to 3096 in. Dia. 3096 in. to 3120 in. Dia. 3120 in. to 3144 in. Dia. 3144 in. to 3168 in. Dia. 3168 in. to 3192 in. Dia. 3192 in. to 3216 in. Dia. 3216 in. to 3240 in. Dia. 3240 in. to 3264 in. Dia. 3264 in. to 3288 in. Dia. 3288 in. to 3312 in. Dia. 3312 in. to 3336 in. Dia. 3336 in. to 3360 in. Dia. 3360 in. to 3384 in. Dia. 3384 in. to 3408 in. Dia. 3408 in. to 3432 in. Dia. 3432 in. to 3456 in. Dia. 3456 in. to 3480 in. Dia. 3480 in. to 3504 in. Dia. 3504 in. to 3528 in. Dia. 3528 in. to 3552 in. Dia. 3552 in. to 3576 in. Dia. 3576 in. to 3600 in. Dia. 3600 in. to 3624 in. Dia. 3624 in. to 3648 in. Dia. 3648 in. to 3672 in. Dia. 3672 in. to 3696 in. Dia. 3696 in. to 3720 in. Dia. 3720 in. to 3744 in. Dia. 3744 in. to 3768 in. Dia. 3768 in. to 3792 in. Dia. 3792 in. to 3816 in. Dia. 3816 in. to 3840 in. Dia. 3840 in. to 3864 in. Dia. 3864 in. to 3888 in. Dia. 3888 in. to 3912 in. Dia. 3912 in. to 3936 in. Dia. 3936 in. to 3960 in. Dia. 3960 in. to 3984 in. Dia. 3984 in. to 4008 in. Dia. 4008 in. to 4032 in. Dia. 4032 in. to 4056 in. Dia. 4056 in. to 4080 in. Dia. 4080 in. to 4104 in. Dia. 4104 in. to 4128 in. Dia. 4128 in. to 4152 in. Dia. 4152 in. to 4176 in. Dia. 4176 in. to 4200 in. Dia. 4200 in. to 4224 in. Dia. 4224 in. to 4248 in. Dia. 4248 in. to 4272 in. Dia. 4272 in. to 4296 in. Dia. 4296 in. to 4320 in. Dia. 4320 in. to 4344 in. Dia. 4344 in. to 4368 in. Dia. 4368 in. to 4392 in. Dia. 4392 in. to 4416 in. Dia. 4416 in. to 4440 in. Dia. 4440 in. to 4464 in. Dia. 4464 in. to 4488 in. Dia. 4488 in. to 4512 in. Dia. 4512 in. to 4536 in. Dia. 4536 in. to 4560 in. Dia. 4560 in. to 4584 in. Dia. 4584 in. to 4608 in. Dia. 4608 in. to 4632 in. Dia. 4632 in. to 4656 in. Dia. 4656 in. to 4680 in. Dia. 4680 in. to 4704 in. Dia. 4704 in. to 4728 in. Dia. 4728 in. to 4752 in. Dia. 4752 in. to 4776 in. Dia. 4776 in. to 4800 in. Dia. 4800 in. to 4824 in. Dia. 4824 in. to 4848 in. Dia. 4848 in. to 4872 in. Dia. 4872 in. to 4896 in. Dia. 4896 in. to 4920 in. Dia. 4920 in. to 4944 in. Dia. 4944 in. to 4968 in. Dia. 4968 in. to 4992 in. Dia. 4992 in. to 5016 in. Dia. 5016 in. to 5040 in. Dia. 5040 in. to 5064 in. Dia. 5064 in. to 5088 in. Dia. 5088 in. to 5112 in. Dia. 5112 in. to 5136 in. Dia. 5136 in. to 5160 in. Dia. 5160 in. to 5184 in. Dia. 5184 in. to 5208 in. Dia. 5208 in. to 5232 in. Dia. 5232 in. to 5256 in. Dia. 5256 in. to 5280 in. Dia. 5280 in. to 5304 in. Dia. 5304 in. to 5328 in. Dia. 5328 in. to 5352 in. Dia. 5352 in. to 5376 in. Dia. 5376 in. to 5400 in. Dia. 5400 in. to 5424 in. Dia. 5424 in. to 5448 in. Dia. 5448 in. to 5472 in. Dia. 5472 in. to 5496 in. Dia. 5496 in. to 5520 in. Dia. 5520 in. to 5544 in. Dia. 5544 in. to 5568 in. Dia. 5568 in. to 5592 in. Dia. 5592 in. to 5616 in. Dia. 5616 in. to 5640 in. Dia. 5640 in. to 5664 in. Dia. 5664 in. to 5688 in. Dia. 5688 in. to 5712 in. Dia. 5712 in. to 5736 in. Dia. 5736 in. to 5760 in. Dia. 5760 in. to 5784 in. Dia. 5784 in. to 5808 in. Dia. 5808 in. to 5832 in. Dia. 5832 in. to 585

TYPE OF SCREEN OR PERFORATION MATERIAL:			7 PVC	10 Asbestos-cement
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS:	From 32 ft. to 72 ft.,	From ft. to ft.
	From ft. to ft.,	From ft. to ft.
GRAVEL PACK INTERVALS:	From 14 ft. to 72 ft.,	From ft. to ft.
	From ft. to ft.,	From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 4 ft. to 14 ft. From 14 ft. to 14 ft. From 14 ft. to 14 ft. From 14 ft. to 14 ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	None Apparent.....

Direction from well? _____ How many feet? _____

[illegible]

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-5-84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 2-20-85 under the business name of Harp Well & Pump Service, Inc. by (signature) Mary Arnold

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.