

PAULS VALLEY 3rd ADD

1 LOCATION OF WATER WELL: County: BETTER Fraction: SW 1/4 NE 1/4 SE 1/4 Section Number: 18 Township Number: T 28 S Range Number: R 3 E

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: RANDY THOMAS
 RR#, St. Address, Box #: 320 COMMENCE AVE 11102
 City, State, ZIP Code: WICHITA, KS (near Rosehill 67133)
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

NW	NE
SW	SE X

4 DEPTH OF COMPLETED WELL: 95 ft. ELEVATION: 90 ft.
 Depth(s) Groundwater Encountered 1. 60 ft. 2. 90 ft. 3. 90 ft.
 WELL'S STATIC WATER LEVEL 30 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was 150 gpm: Well water was 8 in. to 95 ft. and 95 in. to 95 ft.
 Est. Yield 150 gpm: Well water was 8 in. to 95 ft. and 95 in. to 95 ft.
 Bore Hole Diameter 8 in. to 95 ft. and 95 in. to 95 ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded.
 Blank casing diameter 5 in. to 96 ft. Dia. 160 lbs./ft. Wall thickness or gauge No. 12
 Casing height above land surface 12 in. weight 160 lbs./ft.
 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 75 ft. to 95 ft. From 75 ft. to 95 ft.
 GRAVEL PACK INTERVALS: From 20 ft. to 95 ft. From 20 ft. to 95 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 20 ft. From 3 ft. to 20 ft.
 What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
 Direction from well? South How many feet? 150'

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0'	7'	EARTH			
7'	30'	BROWN CLAY			
30'	47'	RED BED			
47'	65'	GRAY SHALE			
65'	95'	SHALEY LIME			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) May 25, 1983 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 424 This Water Well Record was completed on (mo/day/yr) June 20, 83
 under the business name of REISERER WELL DRILLING by (signature) Jerry Reiserer
 INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.