

1 LOCATION OF WATER WELL		Fraction	Section Number	Township Number	Range Number		
County Butler		NE 1/4 NE 1/4 SE 1/4	19	T 28 S	R 3 E		
Distance and direction from nearest town or city? from the corner of Andover Road and 54 Highway, 5.6 miles south, 3 miles west							
2 WATER WELL OWNER: Clifford Nies							
RR#, St. Address, Box # : 9415 E Harry			Board of Agriculture, Division of Water Resources				
City, State, ZIP Code : Wichita, Ks.			Application Number:				
3 DEPTH OF COMPLETED WELL: 72 ft. Bore Hole Diameter: 10 in. to 72 ft., and in. to ft.							
Well Water to be used as:							
☒ Domestic		5 Public water supply		8 Air conditioning			
3 Feedlot		6 Oil field water supply		11 Injection well			
2 Irrigation		7 Lawn and garden only		12 Other (Specify below)			
4 Industrial		10 Observation well					
Well's static water level 11 ft. below land surface measured on 6 month 25 day 84 year							
Pump Test Data : Well water was ft. after hours pumping. gpm							
Est. Yield 15+ gpm: Well water was ft. after hours pumping. gpm							
4 TYPE OF BLANK CASING USED:							
1 Steel		3 RMP (SR)		5 Wrought iron			
☒ PVC		4 ABS		6 Asbestos-Cement			
				7 Fiberglass			
				8 Concrete tile			
				9 Other (specify below)			
Casing Joints: Glued ☒ Clamped Welded Threaded							
Blank casing dia 6 in. to 77 ft., Dia in. to ft., Dia in. to ft.							
Casing height above land surface 18 in., weight lbs./ft. Wall thickness or gauge No 160							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel		3 Stainless steel		5 Fiberglass			
2 Brass		4 Galvanized steel		6 Concrete tile			
				8 RMP (SR)			
				9 ABS			
				10 Asbestos-cement			
				11 Other (specify)			
				12 None used (open hole)			
Screen or Perforation Openings Are:							
1 Continuous slot		3 Mill slot		5 Gauzed wrapped			
2 Louvered shutter		4 Key punched		6 Wire wrapped			
				7 Torch cut			
				8 Saw cut			
				11 None (open hole)			
Screen-Perforation Dia 6 in. to ft., Dia in. to ft., Dia in. to ft.							
Screen-Perforated Intervals: From 27 ft. to 33 ft., From 47 ft. to 77 ft.							
Gravel Pack Intervals: From 20 ft. to 77 ft., From ft. to ft.							
5 GROUT MATERIAL:							
☒ Neat cement		2 Cement grout		3 Bentonite			
4 Other							
Grouted Intervals: From 3.5 ft. to 20 ft., From ft. to ft., From ft. to ft.							
What is the nearest source of possible contamination:							
☒ Septic tank		4 Cess pool		7 Sewage lagoon			
2 Sewer lines		5 Seepage pit		8 Feed yard			
3 Lateral lines		6 Pit privy		9 Livestock pens			
				10 Fuel storage			
				11 Fertilizer storage			
				12 Insecticide storage			
				13 Watertight sewer lines			
				14 Abandoned water well			
				15 Oil well/Gas well			
				16 Other (specify below)			
Direction from well installed per Butler County Zoning ? Water Well Disinfected? Yes ☒ No							
Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, date sample was submitted month day year: Pump Installed? Yes No							
If Yes: Pump Manufacturer's name Model No. HP Volts							
Depth of Pump Intake ft. Pumps Capacity rated at gal./min.							
Type of pump: 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other							
6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on 6 month 25 day 1984 year							
and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No.							
This Water Well Record was completed on 6 month 28 day 1984 year under the business name of Eudge Drilling by (signature) <i>Mehm R. Eudge</i>							
7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
		0	2	top soil	63	72 1/2	gray shale less fissal
		2	12	brownish yellow gray shale	72 1/2	75	dark gray fissal shale
		12	26	Yellow gray shale	75	77	gray clay
		26	27	yellow gray limestone			
		27	38 1/2	yellow gray clay			
		38 1/2	57	gray clay			
		57	59 1/2	gray limestone			
		59 1/2	61	dark gray shale with thin limestone stringers			
		61	63	dark gray fissal shale			
		ELEVATION:					
Depth(s) Groundwater Encountered 1. 26 ft. 2. 57 ft. 3. 72 ft. 4. ft. (Use a second sheet if needed)							
INSTRUCTIONS: Use typewriter or ball point pen, please press firmly and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Water Well Contractors, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.							

OFFICE USE ONLY

T

R

EW

SEC

1/4

1/4

1/4