

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Butler		NW 1/4 NW 1/4 SW 1/4	28	T 28 S	R 30 E
Distance and direction from nearest town or city street address of well if located within city: 1 No 1 East 1/2 No. Roschill, KS					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
City, State, ZIP Code :		Roschill, KS			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 65 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 25 ft. 2. 30 ft. 3. 11-4-83 ft.			
		WELL'S STATIC WATER LEVEL 25 ft. below land surface measured on mo/day/yr 11-4-83			
		Pump test data: Well water was 15-25 gpm: Well water was 30 ft. after 12 hours pumping 15 gpm			
		Est. Yield 15-25 gpm: Well water was 30 ft. after 12 hours pumping 15 gpm			
		Bore Hole Diameter 11 in. to 65 ft., and 65 in. to 65 ft.			
		WELL WATER TO BE USED AS:			
		☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below) ☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes ☒ No ☒ If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued ☒ Clamped ☒ Welded ☐ Threaded ☐			
☐ 1 Steel ☒ 3 RMP (SR) ☐ 2 PVC ☒ 4 ABS		☐ 5 Wrought iron ☐ 8 Concrete tile ☐ 9 Other (specify below) ☐ 6 Asbestos-Cement ☐ 7 Fiberglass			
Blank casing diameter 5 in. to 12 1/8 ft., Dia 1.59 in. to 1.59 ft., Dia 1.59 in. to 1.59 ft., weight 1.59 lbs./ft. Wall thickness or gauge No. SPR-26					
TYPE OF SCREEN OR PERFORATION MATERIAL:		☐ 7 PVC ☐ 10 Asbestos-cement ☐ 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☒ 8 RMP (SR) ☐ 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 9 ABS ☐ 11 Other (specify) ☐ 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		☐ 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole) ☐ 1 Continuous slot ☒ 3 Mill slot ☐ 6 Wire wrapped ☐ 9 Drilled holes ☐ 2 Louvered shutter ☐ 4 Key punched ☐ 7 Torch cut ☐ 10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		From 18 ft. to 65 ft., From 18 ft. to 65 ft., From 18 ft. to 65 ft., From 18 ft. to 65 ft. From 13 ft. to 65 ft., From 13 ft. to 65 ft., From 13 ft. to 65 ft., From 13 ft. to 65 ft.			
GRAVEL PACK INTERVALS:		From 13 ft. to 65 ft., From 13 ft. to 65 ft., From 13 ft. to 65 ft., From 13 ft. to 65 ft.			
6 GROUT MATERIAL:		☐ 1 Neat cement ☒ 2 Cement grout ☐ 3 Bentonite ☐ 4 Other Grout Intervals: From 3 ft. to 13 ft., From 3 ft. to 13 ft., From 3 ft. to 13 ft., From 3 ft. to 13 ft.			
What is the nearest source of possible contamination:		☒ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well ☐ 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well ☐ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below) ☐ 13 Insecticide storage			
Direction from well? NW		How many feet? 85			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	Top Soil			
3	48	Brown Rock.			
48	51	Gray Clay.			
51	65	Gray Shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-4-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 11-4-83 under the business name of Wenger Drilling by (signature) Wenger					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					