


1 LOCATION OF WATER WELL: County: Butler		Fraction: NW 1/4 NW 1/4 NE 1/4	Section Number: 1	Township Number: T 28 S	Range Number: R 4 E																																																
Distance and direction from nearest town or city street address of well if located within city? 2 S of Augusta East 1 1/2 miles																																																					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code : Chas Dickinson RR# 1 Box 165 Augusta, KS 67018			Board of Agriculture, Division of Water Resources Application Number:																																																		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: ft. ELEVATION: Depth(s) Groundwater Encountered 1. 30 ft. 2. 45 ft. 3. 65 ft. WELL'S STATIC WATER LEVEL 30 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield 20 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter: 10 in. to ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes..... No..... If yes, mo/day/yr sample was submitted Water Well Disinfected: Yes..... No.....																																																			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued..... Clamped..... 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded..... Blank casing diameter 5 in. to ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface 12 in., weight 160 lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 70 ft. to 90 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 20 ft. to 90 ft. From ft. to ft.																																																					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 3 ft. to 20 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? How many feet? +200																																																					
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>8</td> <td>Earth</td> <td></td> <td></td> <td></td> </tr> <tr> <td>8</td> <td>20</td> <td>Clay</td> <td></td> <td></td> <td></td> </tr> <tr> <td>20</td> <td>45</td> <td>Gray shale</td> <td></td> <td></td> <td></td> </tr> <tr> <td>45</td> <td>65</td> <td>limestone</td> <td></td> <td></td> <td></td> </tr> <tr> <td>65</td> <td>80</td> <td>Red bed</td> <td></td> <td></td> <td></td> </tr> <tr> <td>80</td> <td>90</td> <td>light gray shale</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>dark gray shale</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>						FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG	0	8	Earth				8	20	Clay				20	45	Gray shale				45	65	limestone				65	80	Red bed				80	90	light gray shale						dark gray shale			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG																																																
0	8	Earth																																																			
8	20	Clay																																																			
20	45	Gray shale																																																			
45	65	limestone																																																			
65	80	Red bed																																																			
80	90	light gray shale																																																			
		dark gray shale																																																			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/19/85 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 424 This Water Well Record was completed on (mo/day/yr) 9/26/85 under the business name of Reisner Well Drilling by (signature) Jerry Reisner INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.																																																					