


Butler

WATER WELL RECORD

Form WWC-5

KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgewick		N 1/2 1/4 NE 1/4 SE 1/4 1/4	27	T 28 S	R 4 E
Distance and direction from nearest town or city, street address of well if located within city?					
Blumington Rd E 77th 1/2 East 1/4 North West Side					
2 WATER WELL OWNER: Ren KAEKEL					
RR#, St. Address, Box #: 11020 E Bellairs					
City, State, ZIP Code: Wichita, KS 67207					
Board of Agriculture, Division of Water Resources					
Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 95 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 75 ft. 2. 65 ft. 3. 85 ft.			
		WELL'S STATIC WATER LEVEL 30 ft. below land surface measured on mo/day/yr 4/28/89			
		Pump test data: Well water was ... ft. after ... hours pumping ... gpm			
		Est. Yield 15 gpm: Well water was ... ft. after ... hours pumping ... gpm			
		Bore Hole Diameter 10 in. to ... ft., and ... in. to ... ft.			
		WELL WATER TO BE USED AS:			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped					
2 PVC 4 ABC 6 Asbestos-Cement 9 Other (specify below) Welded					
7 Fiberglass Threaded					
Blank casing diameter 5 in. to ... ft., Dia ... in. to ... ft., Dia ... in. to ... ft.					
Casing height above land surface 12 in., weight 200 lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)					
12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 75 ft. to 95 ft. From ... ft. to ... ft.					
GRAVEL PACK INTERVALS: From 20 ft. to 95 ft. From ... ft. to ... ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 20 ft. From ... ft. to ... ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage					
Direction from well? DOWN SLOPE EAST					
How many feet? 4100					
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0 10 Earth Clay					
10 25 Yellow Clay					
25 40 Heavy gray shale					
40 60 Dark gray shale					
60 75 Light gray shale					
75 95 Light gray shale					
RECEIVED					
AUG 22 1990					
DIVISION OF ENVIRONMENT					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) August 21, 89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 493 This Water Well Record was completed on (mo/day/yr) August 23, 1989 under the business name of Reiserer Well Drilling by (signature) Jerry Reiserer					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.					