

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: BUTLER		SE 1/4 NE 1/4 NW 1/4	35	T 28 S	R 5 (EW)
Distance and direction from nearest town or city street address of well if located within city? 7 MI. SO. OF LEON AND 1/2 WEST					

2 WATER WELL OWNER: ROSS Boucher		Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # 322 Brierbrook Dr.		Application Number: NA
City, State, ZIP Code CARL JUNCTION MO. 64834		

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 190 ft. ELEVATION: NA	
		Depth(s) Groundwater Encountered 1. 42 ft. 2. . ft. 3. . ft.	
		WELL'S STATIC WATER LEVEL 30 ft. below land surface measured on mo/day/yr 11-7-98	
		Pump test data: Well water was NA ft. after NA hours pumping NA gpm	
		Est. Yield 1 gpm; Well water was . ft. after . hours pumping . gpm	
		Bore Hole Diameter: 9 1/4 in. to 190 ft., and . in. to . ft.	
WELL WATER TO BE USED AS:			
☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes . No ☒ . If yes, mo/day/yr sample was submitted			
Water Well Disinfected? Yes ☒ No			

5 TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded
☒ 2 PVC	4 ABS	7 Fiberglass		Threaded
Blank casing diameter 5 in. to 175 ft., Dia in. to ft., Dia in. to ft.				
Casing height above land surface 18 in., weight 3.364 lbs./ft. Wall thickness or gauge No. SDR 26 .255				
TYPE OF SCREEN OR PERFORATION MATERIAL:				
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:				
1 Continuous slot	☒ 3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
SCREEN-PERFORATED INTERVALS: From 175 ft. to 190 ft., From ft. to ft.				
GRAVEL PACK INTERVALS: From 20 ft. to 190 ft., From ft. to ft.				

6 GROUT MATERIAL: ☒ 1 Neat cement 2 Cement grout ☒ 3 Bentonite 4 Other	
Grout Intervals: From 2 ft. to 20 ft., From ft. to ft., From ft. to ft.	
What is the nearest source of possible contamination:	
1 Septic tank	10 Livestock pens
2 Sewer lines	11 Fuel storage
3 Watertight sewer lines	12 Fertilizer storage
4 Lateral lines	13 Insecticide storage
5 Cess pool	14 Abandoned water well
6 Seepage pit	☒ 15 Oil well/Gas well
7 Pit privy	16 Other (specify below)
8 Sewage lagoon	
9 Feedyard	
Direction from well? SE How many feet? 650 ft. SE	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	TOP SOIL			
2	12	RED CLAY			
12	42	YELLOW LIME			
42	48	GRAY SHALE			
48	54	SANDY SHALE			
54	85	GRAY LIME			
85	97	GRAY SHALE			
97	102	GRAY LIME			
102	110	GRAY SHALE			
110	122	GRAY LIME			
122	142	GRAY SHALE			
142	168	GRAY LIME			
168	185	GRAY SHALE			
185	190	RED SHALE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-9-98 and this record is true to the best of my knowledge and belief. Kansas	
Water Well Contractor's License No. 464	This Water Well Record was completed on (mo/day/yr) 11-11-98
under the business name of WATER WELL SERVICES	by (signature) <i>[Signature]</i>

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.