


1 LOCATION OF WATER WELL: County: <u>Sedowick</u>		Fraction <u>NE 1/4 NE 1/4 NE 1/4</u>	Section Number <u>5</u>	Township Number T <u>29</u> S	Range Number R <u>1</u> <u>E</u>
Distance and direction from nearest town or city street address of well if located within city? <u>7201 S. Broadway, Haysville, KS.</u>					
2 WATER WELL OWNER: <u>Parker Oil Co./Jim Selenke</u> RR#, St. Address, Box #: <u>4343 S. West</u> City, State, ZIP Code: <u>Wichita, Ks. 67217</u> Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: <u>20'</u> ft. ELEVATION: Depth(s) Groundwater Encountered 1. <u>12'</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>11.17</u> ft. below land surface measured on mo/day/yr <u>4-29-96</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm; Well water was ft. after hours pumping gpm Bore Hole Diameter <u>8 1/2"</u> in. to <u>20'</u> ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes <u>No</u> X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>No</u>			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>Clamped</u> <u>2 PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded <u>X</u> Blank casing diameter <u>2.375</u> in. to <u>10'</u> ft. Dia. in. to ft. Dia. in. to SDR <u>13</u> ft. Casing height above land surface <u>Flush Mt.</u> in., weight lbs./ft. Wall thickness or gauge No. <u>SCH 40</u> TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From <u>20'</u> ft. to <u>10'</u> ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From <u>20'</u> ft. to <u>8'</u> ft. From ft. to ft. From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From <u>8'</u> <u>3</u> to <u>4'</u> <u>2</u> ft. From <u>4'</u> <u>2</u> ft. to <u>0'</u> ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage <u>Fueller</u> 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? <u>Southeast</u> How many feet? <u>75'</u>					
FROM TO LITHOLOGIC LOG			FROM TO PLUGGING INTERVALS		
0	.75	Asphalt			
.75	3	Med-dk brn sandy silt, moist to dry, no odor, soft.			
3	6.50	Fine grained sand to silty sand, dry to moist, no odor, well rounded & sorted.			
6.50	12.25	Fine grained sand, dry to moist, no odor. Wet at 12'.			
12.25	20	Pale gray sand & gravel, wet, no odor, poorly sorted, subrounded grains of fine- very coarse grains.			
			F.M. OK'd by Don Taylor		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>4-21-96</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>539</u> This Water Well Record was completed on (mo/day/yr) <u>5-18-96</u> under the business name of <u>JB Environmental Drilling</u> by (signature) <u>James Beeber</u>					