

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction NE 1/4 NE 1/4 NE 1/4	Section Number 5	Township Number T 29 S	Range Number R 1 E
Distance and direction from nearest town or city street address of well if located within city? 7201 S. Broadway, Haysville, KS.					
2 WATER WELL OWNER: Parker Oil Co./Jim Selenke RR#, St. Address, Box # : 4343 S. West City, State, ZIP Code : Wichita, KS. 67217			Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 20' ft. ELEVATION: Depth(s) Groundwater Encountered 1. 11 1/2' ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 11.60 ft. below land surface measured on mo/day/yr 4-29-96 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 1/2" in. to 20' ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2.375 in. to 10' ft. Dia in. to ft. Dia in. to SDR 13 ft. Casing height above land surface Flush Mt. in. weight lbs./ft. Wall thickness or gauge No. SCH. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 3 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 20' ft. to 10' ft. From ft. to ft. GRAVEL PACK INTERVALS: From 20' ft. to 8' ft. From ft. to ft.					
6 GROUT MATERIAL: Grout Intervals: From 8' ft. to 4' ft. From 4' ft. to 0' ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage Framer 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below) Direction from well? Northeast How many feet? 110'					
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS			
0	.50	Asphalt			
.50	3	Dk brn sandy silt, soft, moist, earthy odor, friable, fine grained sand.			
3	6	Med-lt brn fine grained silty sand, no odor, dry.			
6	11	Fine grained dry sand, well rounded & sorted, no odor.			
11	20	Gray river bottom sand, no odor, wet at 11 1/2', fine-coarse grained, poorly sorted.			
F.M. OK'd by Don Taylor					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-25-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 5-18-96 under the business name of JB Environmental Drilling by (signature) James Becker					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					