

1 LOCATION OF WATER WELL: County: Sedgwick NE 1/4 NE 1/4 SW 1/4 Section Number 10 Township Number 29 Range Number 10  
Distance and direction from nearest town or city street address of well if located within city?  
8400 Kansas

2 WATER WELL OWNER: Curtis Hampton & Sons  
RR#, St. Address, Box #: 1832 S. Meridian  
City, State, ZIP Code: Wichita, KS 67233  
Board of Agriculture, Division of Water Resources  
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
N  
NW NE  
SW SE  
S  
W E  
1 Mile

4 DEPTH OF COMPLETED WELL: 36 ft. ELEVATION: 12-18-97  
Depth(s) Groundwater Encountered: 12 ft. below land surface measured on mo/day/yr  
WELL'S STATIC WATER LEVEL: 12 ft. below land surface measured on mo/day/yr  
Pump test data: Well water was 20 gpm Well water was 11 in. to 36 ft. after 36 hours pumping  
Est. Yield: 20 gpm Well water was 11 in. to 36 ft. after 36 hours pumping  
Bore Hole Diameter: 11 in. to 36 ft. and 36 in. to 36 ft.  
WELL WATER TO BE USED AS:  
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:  
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped  
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
Blank casing diameter: 5 in. to 26 ft. Dia 2.40 in. to 26 ft. Dia 160 PSI  
Casing height above land surface: 12 in. weight 2.40 lbs./ft. Wall thickness or gauge No. 160 PSI  
TYPE OF SCREEN OR PERFORATION MATERIAL:  
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement  
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)  
SCREEN OR PERFORATION OPENINGS ARE:  
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
2 Louvered shutter 4 Key punched 7 Torch cut 9 Drilled holes 10 Other (specify)  
SCREEN-PERFORATED INTERVALS: From 26 ft. to 36 ft. From 26 ft. to 36 ft.  
GRAVEL PACK INTERVALS: From 12 ft. to 36 ft. From 12 ft. to 36 ft.

6 GROUT MATERIAL: 3 1 Neat cement 12 2 Cement grout 3 Bentonite 4 Other  
Grout Intervals: From 3 ft. to 12 ft. From 3 ft. to 12 ft. From 3 ft. to 12 ft. From 3 ft. to 12 ft.  
What is the nearest source of possible contamination:  
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
13 Insecticide storage  
Direction from well? northeast How many feet? 600

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS  
0 14 clay  
14 36 fine to medium sand

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-18-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 12-19-97 under the business name of Weninger Drilling Inc. by (signature) Thelma George

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.