

1 LOCATION OF WATER WELL:		FRACTION		Section Number		Township Number		Range Number	
Sedgwick		SW 1/4 NE 1/4 SE 1/4		5		T 29 S		R 1E E/W	
Distance and direction from nearest town or city street address of well if located within city?									
71st S. & Broadway, 3/8 m. S., 1/4 W. Haysville, Kansas									
WATER WELL OWNER: HAYSVILLE, CITY OF									
RR#, ST. ADDRESS, BOX #: 200 W. Grand									
CITY, STATE, ZIP CODE: Haysville, Kansas 67060									
Board of Agriculture, Division of Water Resource									
Application Number: 20010245									
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 40 ft. ELEVATION:							
↑ N 1 mile W ↓ S		Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.							
NW NE SW SE		WELL'S STATIC WATER LEVEL 12 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 11-20-2001							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield gpm Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 12 in. to 40 ft. and in. to ft.							
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well							
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							
		Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes X No							
5 TYPE OF CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped									
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (Specify below) Welded									
Blank casing Diameter 8 in. to 20 ft., Dia in. to ft., Dia in. to ft.									
Casing height above land surface 12 in., weight 5.52 lbs. / ft. Wall thickness or gauge No. .332									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENING ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes									
7 Torch cut 10 Other (specify)									
SCREEN-PERFORATION INTERVALS: from 20 ft. to 37 ft., From ft. to ft.									
GRAVEL PACK INTERVALS: from 20 ft. to 40 ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug									
Grout Intervals: From ft. to ft. From ft. to ft. From 0 ft. to 20 ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandon water well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)									
13 Insecticide storage None Apparent									
Direction from well? How many feet?									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 10 fine sand									
10 25 medium coarse sand									
25 26 clay									
26 40 coarse sand									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-20-2001 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 11-21-2001									
Under the business name of Harp Well & Pump Service, Inc by (signature) Todd S. Harp									