

1 LOCATION OF WATER WELL:		FRACTION		Water Well Record Form WWC-5 KSA 82a-1212		Section Number		Township Number		Range Number	
Sedgwick		SW 1/4 NW 1/4 NW 1/4		6		T 29 S		R 1E		E/W	
Distance and direction from nearest town or city street address of well if located within city?											
252 Peachwood Haysville, Kansas											
WATER WELL OWNER: MC Cauley, Mike											
RR#, ST. ADDRESS, BOX #: 252 Peachwood											
CITY, STATE, ZIP CODE: Haysville, Kansas											
Board of Agriculture, Division of Water Resource											
Application Number:											
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:											
4 DEPTH OF COMPLETED WELL 61 ft. ELEVATION:											
Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.											
WELL'S STATIC WATER LEVEL 40 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 4-19-2002											
Pump test data: Well water was ft. after hours pumping gpm											
Est. Yield gpm: Well water was ft. after hours pumping gpm											
Bore Hole Diameter 12 in. to 61 ft. and in. to ft.											
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well											
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)											
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well											
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted											
Water Well Disinfected? Yes X No											
5 TYPE OF CASING USED:											
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped											
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (Specify below) Welded											
7 Fiberglass SDR-26 Threaded											
Blank casing Diameter 5 in. to 41 ft., Dia in. to ft., Dia in. to ft.											
Casing height above land surface 12 in., weight 2.35 lbs. / ft. Wall thickness or gauge No. .214											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)											
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)											
SCREEN OR PERFORATION OPENING ARE:											
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)											
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes											
7 Torch cut 10 Other (specify)											
SCREEN-PERFORATION INTERVALS: from 41 ft. to 61 ft., From ft. to ft.											
GRAVEL PACK INTERVALS: from 24 ft. to 61 ft., From ft. to ft.											
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug											
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to ft.											
What is the nearest source of possible contamination:											
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandon water well											
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well											
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)											
13 Insecticide storage											
Direction from well? South How many feet? 20											
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS											
0 3 topsoil											
3 32 clay											
32 42 fine sand											
42 61 medium sand											
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-19-2002 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 4-22-2002 Under the business name of Harp Well & Pump Service, Inc by (signature) Todd S. Harp											