

1 LOCATION OF WATER WELL: NE 1/4 SW 1/4 NE 1/4 Section 4 Township 29S Range 1E Distance and direction from nearest town or city street address of well if located within city? 7519 S. Pattie

2 WATER WELL OWNER: Paul Schmiedler RR#, St. Address, Box # : City, State, ZIP Code : Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing section box with X in NE quadrant]

4 DEPTH OF COMPLETED WELL 36 ft. ELEVATION: 12-24-03 ft. Depth(s) Groundwater Encountered: 1 10 ft. 2 12-24-03 ft. WELL'S STATIC WATER LEVEL: 10 ft. below land surface measured on mo/day/yr 12-24-03 Pump test data: Well water was 30 ft. after 30 hours pumping 30 gpm Est. Yield: 30 gpm Well water was 30 ft. after 30 hours pumping 30 gpm WELL WATER TO BE USED AS: 1 Domestic 2 Irrigation 3 Feedlot 4 Industrial 5 Public water supply 6 Oil field water supply 7 Domestic (lawn & garden) 8 Air conditioning 9 Dewatering 10 Injection well 11 Other (Specify below) 12 Other (Specify below)

5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued X Clamped Welded Threaded

Blank casing diameter 12 in. to 24 in. Dia 2.40 in. to 1600 psi Casing height above land surface 12 in., weight 2.40 lbs./ft. Wall thickness or guage No. 1600 psi TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless Steel 4 Galvanized Steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-Cement 11 Other (Specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)

SCREEN-PERFORATED INTERVALS: From 26 ft. to 36 ft. From 26 ft. to 36 ft. From 26 ft. to 36 ft. From 26 ft. to 36 ft. GRAVEL PACK INTERVALS: From 26 ft. to 36 ft. From 26 ft. to 36 ft. From 26 ft. to 36 ft. From 26 ft. to 36 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 3 ft. to 26 ft. From 3 ft. to 26 ft. From 3 ft. to 26 ft. From 3 ft. to 26 ft. What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)

Direction from well? north How many feet? 30

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-24-03 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 318 This Water Well Record was completed on (mo/day/year) 12-24-03 under the business name of Weninger Drilling Inc by (signature) Michael Gorker

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.