

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Sedgwick</u>		<u>NE 1/4 NW 1/4 SW 1/4</u>	<u>10</u>	T <u>29</u> S <u>0</u>	R <u>1</u> E <u>W</u>
Distance and direction from nearest town or city street address of well if located within city? <u>8450 S. Ash</u>					
2 WATER WELL OWNER:					
RR#, St. Address, Box # : City, State, ZIP Code : <u>Smith 3 Co</u>			Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL <u>30</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL <u>12</u> ft. below land surface measured on mo/day/yr <u>8-30-04</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield <u>25</u> gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: ☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) ☐ Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? <u>Yes</u> No			
5 TYPE OF BLANK CASING USED:					
1 Steel ☒ 2 PVC 3 RMP (SR) 4 ABS		5 Wrought iron 6 Asbestos-Cement 7 Fiberglass		8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued <u>X</u> Clamped Welded Threaded	
Blank casing diameter <u>5</u> in. to <u>20</u> ft. Dia		Blank casing height above land surface <u>12</u> in., weight <u>2.40</u> lbs./ft. Wall thickness or gauge No. <u>160 psi</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 2 Brass 3 Stainless Steel 4 Galvanized Steel		5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS		10 Asbestos-Cement 11 Other (Specify) 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 2 Louvered shutter ☒ 3 Mill slot 4 Key punched		5 Gauzed wrapped 6 Wire wrapped 7 Torch cut		8 Saw cut 9 Drilled holes 10 Other (specify) ft. 11 None (open hole)	
SCREEN-PERFORATED INTERVALS: From <u>20</u> ft. to <u>30</u> ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>12</u> ft. to <u>30</u> ft., From ft. to ft.					
6 GROUT MATERIAL:					
1 Neat cement 2 Cement grout 3 Bentonite 4 Other		Grout Intervals: From <u>3</u> ft. to <u>12</u> ft., From ft. to ft.			
What is the nearest source of possible contamination:					
1 Septic tank 2 Sewer lines ☒ 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit		7 Pit privy 8 Sewage lagoon 9 Feedyard		10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)	
Direction from well? <u>East</u>		How many feet? <u>40</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>3</u>	<u>Top Soil</u>			<u>RECEIVED</u>
<u>3</u>	<u>30</u>	<u>Med Sand</u>			<u>SEP 07 2004</u>
					<u>BUREAU OF WATER</u>
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1)</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>8-30-04</u> and this record is true to the best of my knowledge and belief. Kansas Water Contractor's Licence No. <u>318</u> This Water Well Record was completed on (mo/day/yr) <u>9-1-04</u> under the business name of <u>Weninger Drilling Inc.</u> by (signature) <u>[Signature]</u>					