

1) LOCATION OF WATER WELL: County: SEDGWICK Fraction: NE 1/4 SW 1/4 NE 1/4 Section Number: 9 Township Number: 29 S Range Number: 1 EW

Distance and direction from nearest town or city street address of well if located within city?
1324 E 82nd St. South Wichita Kansas 67233

2) WATER WELL OWNER: KEVIN LITZNER
RR#, St. Address, Box #: 1230 10th WILD
City, State, ZIP Code: Wichita, Kansas 67216

Board of Agriculture, Division of Water Resources
Application Number:

3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4) DEPTH OF COMPLETED WELL: 30 ft. ELEVATION: 8-25-86
Depth(s) Groundwater Encountered 1. 10 ft. 2. 10 ft. 3. 10 ft.
WELL'S STATIC WATER LEVEL 10 ft. below land surface measured on mo/day/yr 8-25-86
Pump test data: Well water was 10 ft. after 2 hours pumping 40 gpm
Est. Yield 60 gpm: Well water was 10 ft. after 2 hours pumping 40 gpm
Bore Hole Diameter 10 in. to 30 ft., and 30 in. to 30 ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
Was a chemical/bacteriological sample submitted to Department? Yes ✓ No ✓; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes ✓ No ✓

5) TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ✓ Clamped ✓
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded ✓
Blank casing diameter 5 in. to 12 ft., Dia. 5 in. to 12 ft., Dia. 5 in. to 12 ft., Dia. 5 in. to 12 ft., Dia.
Casing height above land surface 2.4 in., weight 2.37 lbs./ft. Wall thickness or gauge No. 250
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 12 ft. to 30 ft., From 12 ft. to 30 ft., From 12 ft. to 30 ft., From 12 ft. to 30 ft.
GRAVEL PACK INTERVALS: From 10 ft. to 30 ft., From 10 ft. to 30 ft., From 10 ft. to 30 ft., From 10 ft. to 30 ft.

6) GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 0-3' SURFACE SOIL
Grout Intervals: From 3 ft. to 10 ft., From 3 ft. to 10 ft., From 3 ft. to 10 ft., From 3 ft. to 10 ft.
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
Direction from well? EAST How many feet? 75

7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-25-86 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 2437 This Water Well Record was completed on (mo/day/yr) 8-25-86 under the business name of Ralph Metzger Well Digger Drilling

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.