


1 LOCATION OF WATER WELL: County: SEPTAGWICK		Fraction SE 1/4 NW 1/4 SE 1/4	Section Number 12	Township Number T 29 S	Range Number R 1 E/M
Distance and direction from nearest town or city street address of well if located within city? 330 S Baltimore, Ocray Kansas					
2 WATER WELL OWNER: RR#, St. Address, Box # : Box 2159 City, State, ZIP Code : Dallas TX		Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 46' ft. ELEVATION: Depth(s) Groundwater Encountered 1. 45' ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 11" in. to 46' ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 1 Domestic 2 Irrigation 3 Feedlot 4 Industrial 6 Oil field water supply 7 Lawn and garden only 8 Air conditioning 9 Dewatering 10 Monitoring well 11 Injection well 12 Other (Specify below) Soil Vent Point Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes NO			
5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC Blank casing diameter 4 in. to 31' ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No. sch 40		5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued Clamped Welded X Threaded TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 11 None (open hole) 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 46 ft. to 31' ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 46 ft. to 29' ft., From ft. to ft. From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement Grout Intervals: 3 From 29 ft. to 26 ft., 2 From 26 ft. to 5 ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)		Direction from well? EAST How many feet? 1 ft			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	35	CLAY - silty CLAYS			
35	46	SANDY CLAYS AND SILTY SANDS			
CASING Height VARIANCES Requested - High traffic Area					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-24-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 517 This Water Well Record was completed on (mo/day/yr) 9-29-92 under the business name of GROUNDWATER Technology by (signature) Dennis White					