	WATER WELL	RECORD F	orm WWC-	5 KSA 82a-12	212		
1 LOCATION OF WATER WELL:	FRACTION	_	SECTION		HIP NUMBER	RANGE NU	MBER
Sedgwick	NE 1/4 NE	E 1/4 SW	1/4 5	Т	29 s	R 1E	E/W
Distance and direction from nearest town or cit	ty street address of well if locat	ed within city?					
1324 E. Southbrooke	,	Vichita, Kansas	s				
2 WATER WELL OWNER: KE	ATING, Jennie						
	4 E. Southbrooke				Board of Agri	culture, Division of Wa	iter Resource
CITY, STATE: Wid	chita, Kansas		ZIP CC	DDE:	Application Num	nber:	
3 LOCATE WELL'S LOCATION 4	DEPTH OF COMPLETED	WELL: 40) ft.	ELEVATION	:		
WITH AN "X" IN SECTION BOX:	•		ft.		ft.		ft.
1	epth of groundwater Enco					0/22/	
	VELL'S STATIC WATER L			AND SURFACE MEA			10
NW NE	Pump tes	t data: Well wat	er was	ft. after	hours	of pumping @	gpm
	Est. Yield: gr	om Well wat	er was	ft. after	hours	of pumping @	gpm
₩ W E	Bore Hole Diameter	12 in.	to 40	ft and	in.	to	ft.
1 1 1 1	VELL WATER TO BE USE	D AS:			9. Dewateri	ng 11. Inject	ion well
SW SE	1. Domestic 3. Feedl	ot 5. Public wa	ter supply 📿	Lawn and garden o		12. Other (Spe	ecify below)
	2. Irrigation 4. Indus			Air conditioning	10. Monitorii	•	
s	Was a chemical/bacteriological	al sample submitted to D	Department?	YES NO		what mo/day/yr wa	-
	submitted			Was Water Well Dis	infected? (YES N	
5 TYPE OF CASING USED:	5. Wrought Iron	7. Fiberglass	9. Other ((Specify below) C	ASING JOINTS: (Glued	Threaded
1. Steel 3. RPM (S	SR)	0 C	SDR-20	6		Welded	Clamped
2. PVC 4. ABS	6. Asbestos-Cem	ent 8. Concrete ti	ie SEISE	-			
Blank casing diameter 5	in. to 30	ft., Dia.	in.	to ft.,	Dia.	in. to	ft.
Casing height above land surface:	12 in.,	Weight:	2.35 lbs. / f	ft. Wall	thickness or gaug	ge No214	
TYPE OF SCREEN OR PERFORATION	-						
1. Steel 3. Stainless Steel	5. Fiberglass	7. PVC	9. ABS	11.	Other (specify)		
2. Brass 4. Galvanized	6. Concrete Tile	8. RMP (SR)	10 Ashes	tos-Cement 12.	None used (open	hole)	
		(2)	,		,,,	,	
SCREEN OR PERFORATION OPENIN						44 Nassatis	
1. Continuous slot 3. Mill s	slot 5. Gauze	d wrapped	7. Torch o	cut 9. Di	rilled holes	11. None (or	en hole)
2. Louvered shutter 4. Key	punched 6. Wire w	rapped	8. Saw cu	10.0	ther (specify)		
SCREEN - PERFORATION INTERVAL	. From 3 0) ft. to	40 ft	F			
SCREEN - PERFORATION INTERVAL			,	From	ft.	to	ft.
	From	ft. to	ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS:	From 24	ft. to	40 ft.,	From	ft.	to	ft.
	From	ft. to	ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1 No.		3	2.00	-414-	Other hent	onito hala nlu	
1. West content of the plag							
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to What is the nearest source of possible contamination:						ft.	
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens				ns 13. inse	cticide storage	15. Oil well/Ga	s well
1. Septic talik 4. Lateral lines 9. Source Indoor 11. File storage 44. About 2						cify below)	
2. Sewer mies 0. Seas Foot							
No. 41	page pit 9. Feed	yard	2. Fertilizer sto	-	35	C4	
Direction from well? North	LITUOL COICLO	_			many feet? 35		
From To	LITHOLOGIC LO	G	From	То	LITHOLC	GIC LOG	
0 3 topsoil							
3 8 clay							
8 15 fine sand			 				
15 40 medium san	ıd		 				
			 				
			 	 }			
			 				
			 				
			 				
			<u>L</u>				
Contractor's or Landowner's Cert	16-4	as 1 Constructed	2. recons	structed or 3.	plugged	under my jurisdiction	on and
	attication: This water well w						
was completed on (mo/day/year)	8/23/16		is true to the bes	t of my knowledge an	d belief.		
was completed on (mo/day/year)	8/23/16	and this record		,		1/16	
was completed on (mo/day/year) Kansas Water Well Contractor's Lice	8/23/16	and this record		mpleted on (mo/day/y	rear) 8/2	24/16	
	8/23/16 ense No. 236	and this record This water we		mpleted on (mo/day/y	rear) 8/2	4/16 . Harp	