	WATER WEL	L RECORD	orm WV	VC-5 KS	SA 82a-1212	2		
1 LOCATION OF WATER WELL:	FRACTION			TION NUMBER			RANGE NUM	
Sedgwick Sedgwick		1/4 SE	1/4		T 29	S	R 1E	E/W
Distance and direction from nearest town or cit 2104 W. School House	ty street address of well if lo Haysville, K							
	PE, Jared	kansas						
RR#,ST. ADDRESS,BOX #: 2104 W. School House								
CITY, STATE: Hay	ysville, Kansas			P CODE:		Application Num	nber:	
	DEPTH OF COMPLET	TED WELL: 7	0 ft.		ELEVATION:			
WITH AN "X" IN SECTION BOX:	epth of groundwater En		ft.			ft.		ft.
v	VELL'S STATIC WATER			W LAND SU	RFACE MEASUF			
NW NE	·	test data: Well wa			ft. after		of pumping @	gpm gpm
W W E	Est. Yield: Bore Hole Diameter	gpm Well wa	ater was to 7	70 ft.	ft. after and	in.	to	ft.
	VELL WATER TO BE U	JSED AS:				9. Dewateri	44 1 1	
swse	1. Domestic 3. Fee	edlot 5. Public w	ater supply	7. Lawn a	nd garden only	>	12. Other (Spe	cify below)
	-		vater supply			10. Monitorin	n g well what mo/day/yr wa	s sample
S s	Was a chemical/bacteriolog submitted	gical sample submitted to	Department?	YES Was W	ater Well Disinfe		YES NO	•
5 TYPE OF CASING USED:	5. Wrought Iron	n 7. Fiberglass	9. O	ther (Specify	below) CASII	NG JOINTS: (Glued 1	hreaded
1. Steel 3. RPM (S	SR)		SDI	R-26	,		Welded	Clamped
2. PVC 4. ABS	6. Asbestos-Ce		ui c			• -		64
Blank casing diameter 5	in. to 50	•	in.	to	,		in. to	ft.
Casing height above land surface:	12 in.,	Weight:	2.35 II	os. / ft.	Wall thic	kness or gaug	ge No214	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)								
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)								
SCREEN OR PERFORATION OPENIN	NGS ARE:							
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)								en hole)
2. Louvered shutter 4. Key	punched 6. Wire	e wrapped	8. Sa	w cut	10. Other	r (specify)		
SCREEN - PERFORATION INTERVAL	- From	50 ft. t	70	ft.,	From	ft.	to	ft.
	From	ft. t		ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS:	From	24 ft.	o 70	ft.,	From	ft.	to	ft,
	From	ft, t	0	ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1. Nea		2. Cement Grout		3. Bentonite			onite hole plug	
Grout Intervals: From 4		24 ft., From	ft.	to	ft.,	From	ft. to	• ft.
What is the nearest source of possible	7 D:	t privo	10. Livestoo				15 Oil well/Ga	s well
1. Septic tank 4. Lateral lines 9. Source legeon 11. Fuel sto					13. Insecticide storage 15. Oil well/Gas well 14. Abandon water well 16. Other (specify below)			
2. Sewer lines 5. Cess			12. Fertilize	•	14. Abando	II Water Well		· ´
3. Watertight sewer line 6. Seepage pit 9. Feed yard 1: Direction from well? East			12. Perunze	Storage	How many feet? 10 ft. plus			
From To	LITHOLOGIC L	_OG	From	То			GIC LOG	
0 3 topsoil								
3 24 clay								
24 40 fine sand 40 70 medium san	d							
70 median san								
			-					
				 				
			-					
7 Contractor's or Landowner's Cert	ification: This water we	II was 1. constructe	2, re	constructed	or 3. p	lugged	under my jurisdictio	n and
was completed on (mo/day/year)	5/6/19	and this record	is true to the	e best of my l	knowledge and b	elief.		
Kansas Water Well Contractor's Lice	ense No. 236				on (mo/day/year		8/19	
under the business name of Harp Well and Pump Service by (signature) Todd S. Harb								