

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		NE ¼ NE ¼ SW ¼	1	T 29 S	R 1 EW
Distance and direction from nearest town or city street address of well if located within city? 1001 N. Buckner, Derby, Kansas					
2 WATER WELL OWNER:		Kwik Shop			
RR#, St. Address, Box # :		734 East 4th			
City, State, ZIP Code :		Hutchinson, Ks. 67504			
		Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 70 ft. ELEVATION: 1323.09 TOC			
A diagram showing a section box divided into four quadrants labeled NW, NE, SW, SE. An 'X' is marked in the center where the diagonals intersect.		Depth(s) Groundwater Encountered 1. 64 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 65 ft. below land surface measured on mo/day/yr 02-12-93			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 7 5/8 in. to 70 ft., and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		Water Well Disinfected? Yes No X			
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped					
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded					
Blank casing diameter 2 in. to 60 ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)					
SCREEN OR PERFORATION OPENINGS ARE:		12 None used (open hole)			
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
SCREEN-PERFORATED INTERVALS: From 60 ft. to 70 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 58 ft. to 70 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 56 ft., From 56 ft. to 58 ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
Direction from well? northeast		How many feet? 140			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	CLAY, DK BRN			
5	24	CLAY, MED RD, TR SAND, CALICHE			
24	42	CLAY, MOD RD TO LT BRN, SILTY			MW15
42	55	CLAY, LT BRN, SILTY, TR CALICHE			Tag Number 00087922
55	61	SAND, LT BRN, CLAYEY			
61	70	SAND, GREYISH WHITE, CLAYEY			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 02-12-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 06-22-93 under the business name of GeoCore Services, Inc. by (signature) <i>[Signature]</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					