


SW NE NW SW

WATER WELL RECORD

Form WWC-5

KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number						
County: Sedgwick		NE 1/4	1	T 29 S	R 10 E/W						
Distance and direction from nearest town or city street address of well if located within city? 7615 McIntosh Derby KS											
2 WATER WELL OWNER: Monte V. Vardro 7621 McIntosh Derby KS 67037											
Board of Agriculture, Division of Water Resources Application Number:											
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 50 ft. ELEVATION: 1-2392									
		Depth(s) Groundwater Encountered 1. 39 ft. 2. 50 ft. 3. 50 ft. WELL'S STATIC WATER LEVEL 39 ft. below land surface measured on mo/day/yr 1-2392 Pump test data: Well water was 11 gpm. Well water was 50 ft. after 11 hours pumping 1-2392 gpm Est. Yield 11 gpm. Well water was 50 ft. after 11 hours pumping 1-2392 gpm Bore Hole Diameter 11 in. to 50 ft. and 50 in. to 50 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No									
5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded Blank casing diameter 5 in. to 25 ft. Dia 25 in. to 25 ft. Dia 25 in. to 25 ft. Dia Casing height above land surface 12 in. weight 260 lbs./ft. Wall thickness or gauge No. 160 PVC TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 25 ft. to 50 ft. From 25 ft. to 50 ft. From 25 ft. to 50 ft. GRAVEL PACK INTERVALS: From 21 ft. to 50 ft. From 21 ft. to 50 ft. From 21 ft. to 50 ft.											
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout intervals: From 3 ft. to 21 ft. From 3 ft. to 21 ft. From 3 ft. to 21 ft. What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? Southwest How many feet? 100											
FROM		TO		LITHOLOGIC LOG		FROM		TO		PLUGGING INTERVALS	
0		2		top soil							
2		25		clay							
25		32		med sand							
32		50		Shale							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-23-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 1-23-92 under the business name of Werninger Drilling Inc. by (signature) Dan H. Werninger											
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.											