

1 LOCATION OF WATER WELL: County: Sedgwick Fraction: SW 1/4 NE 1/4 SE 1/4 Section Number: 3 Township Number: T 29 S Range Number: R 1 E Distance and direction from nearest town or city: 1/2 West 1/2 No Derby KS.

2 WATER WELL OWNER: RR#: St. Address, Box #: 4151, So. Ridge Rd, Wichita, KS City, State, ZIP Code: Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the SE section]

4 DEPTH OF COMPLETED WELL: 38 ft. ELEVATION: 7-4-84 ft. Depth(s) Groundwater Encountered: 1. 14 ft. 2. 14 ft. 3. 20 ft. WELL'S STATIC WATER LEVEL: 14 ft. below land surface measured on mo/day/yr Pump test data: Well water was 14 ft. after 12 hours pumping 200 gpm Est. Yield: 200 gpm: Well water was 14 ft. after 12 hours pumping 200 gpm Bore Hole Diameter: 14 in. to 38 ft. and 38 in. to 38 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 12 Other (Specify below) 2 Irrigation 3 Feedlot 6 Oil field water supply 9 Dewatering 10 Observation well 7 Lawn and garden only Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded Blank casing diameter: 8 in. to 24 ft. Dia. 12 in. to 3.40 lbs./ft. Wall thickness or gauge No. 160 PSI Casing height above land surface: 12 in. weight TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) 7 Torch cut SCREEN-PERFORATED INTERVALS: From 24 ft. to 38 ft. From 10 ft. to 38 ft. GRAVEL PACK INTERVALS: From 10 ft. to 38 ft. From 10 ft. to 38 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 10 ft. From 10 ft. to 38 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage How many feet? Direction from well? OPEN FIELD

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-4-84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 7-8-84 under the business name of Wm. J. Pully by (signature) Wm. J. Pully

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.