


1 LOCATION OF WATER WELL:		FRACTION		KSA 82a-1212		Section Number		Township Number		Range Number	
Sedgwick		SE 1/4 SE 1/4 SE 1/4		3		T 29 S		R 1E E/W			
Distance and direction from nearest town or city street address of well if located within city?											
3010 E. 79th S. Wichita, Kansas											
2 WATER WELL OWNER:		MAHONEY, Paul									
RR#, ST. ADDRESS, BOX #:		3010 E. 79th S.									
CITY, STATE, ZIP CODE:		Wichita, Kansas									
Board of Agriculture, Division of Water Resource											
Application Number:											
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 40 ft. ELEVATION:									
		Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.									
		WELL'S STATIC WATER LEVEL 13 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 06/04/1993									
		Pump test data: Well water was ft. after hours pumping gpm									
		Est. Yield gpm: Well water was ft. after hours pumping gpm									
		Bore Hole Diameter 12 in. to 40 ft. and in. to ft.									
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well									
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)									
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well									
		Was a chemical/bacteriological sample submitted to Department? Yes No X ; if yes, mo/day/yr sample was submitted									
		Water Well Disinfected? Yes X No									
5 TYPE OF CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped									
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (Specify below) Welded									
2 PVC 4 ABS		7 Fiberglass SDR-26 Threaded									
Blank casing Diameter 5 in. to 30 ft., Dia in. to ft., Dia in. to ft.											
Casing height above land surface 12 in., weight 2.35 lbs. / ft. Wall thickness or gauge No. .214											
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement									
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)											
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)											
SCREEN OR PERFORATION OPENING ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes											
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)											
SCREEN-PERFORATION INTERVALS: from 30 ft. to 40 ft., From ft. to ft.											
GRAVEL PACK INTERVALS: from 24 ft. to 40 ft., From ft. to ft.											
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other											
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.											
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandon water well									
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well											
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)											
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage											
Direction from well? How many feet?		None Apparent									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS											
0 3 topsoil											
3 9 clay											
9 21 fine sand											
21 40 medium sand											
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 06/04/1993 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 06/15/93 Under the business name of Harp Well & Pump Service, Inc. by (signature) Jane Frederick											
542											