

1 LOCATION OF WATER WELL: Fraction NW 1/4 SW 1/4 SE 1/4 Section Number 4 Township Number 29 Range Number 10
County: Sedg. Distance and direction from nearest town or city street address of well if located within city?
2 WATER WELL OWNER: Jim Ryman RR#, St. Address, Box #: 7359 S 2DA City, State, ZIP Code: WICH, KS, 67301 Board of Agriculture, Division of Water Resources Application Number:
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with an 'X' in the center section, SE of the NW corner.] 4 DEPTH OF COMPLETED WELL: 35 ft. ELEVATION: 1150
Depth(s) Groundwater Encountered: 1. 15 ft. 2. 3-16-92 ft. 3. 10 ft.
WELL'S STATIC WATER LEVEL: 15 ft. below land surface measured on mo/day/yr 3-16-92
Pump test data: Well water was 15 ft. after 2 hours pumping 10 gpm
Est. Yield: 30 gpm: Well water was 15 ft. after 2 hours pumping 10 gpm
Bore Hole Diameter: 10 in. to 35 ft., and in. to ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes X No
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
Blank casing diameter: 5 in. to 25 ft. Dia. in. to ft. Dia. in. to ft.
Casing height above land surface: 12 in. weight 2.6 lbs./ft. Wall thickness or gauge No. SRA 26
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 25 ft. to 35 ft. From ft. to ft.
GRAVEL PACK INTERVALS: From 25 ft. to 15 ft. From ft. to ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 2 ft. to 15 ft. From ft. to ft. From ft. to ft.
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
Direction from well? How many feet? None noted
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS
0 2 TOP SOIL
2 18 FINE SAND
18 35 MED SAND