

1 LOCATION OF WATER WELL: County: SEDGWICK NW 1/4 SE 1/4 SW 1/4 Section Number 5 Township Number T 29 S Range Number R 1 EW

Distance and direction from nearest town or city street address of well if located within city? 7830 SHADY CREEK CT. WICHITA KS 67233

2 WATER WELL OWNER: DON BATSON RR#, St. Address, Box #: 7830 SHADY CREEK CT. City, State, ZIP Code: WICHITA KS 67233

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the SW section]

4 DEPTH OF COMPLETED WELL: 29 ft. ELEVATION: 9-16-90

WELL'S STATIC WATER LEVEL: 12 ft. below land surface measured on mo/day/yr 9-16-90

Pump test data: Well water was 12 ft. after 2 hours pumping 40 gpm

Est. Yield 60 gpm: Well water was 12 ft. after 2 hours pumping 40 gpm

Bore Hole Diameter 11 in. to 27 ft. and in. to ft.

WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped

2 PVC 4 ABS 7 Fiberglass 9 Other (specify below) Welded Threaded

Blank casing diameter 5 in. to 20 ft. Dia in. to ft. Dia in. to ft.

Casing height above land surface 14 in. weight 2.37 lbs./ft. Wall thickness or gauge No. 250

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)

7 Torch cut

SCREEN-PERFORATED INTERVALS: From 20 ft. to 29 ft. From ft. to ft.

GRAVEL PACK INTERVALS: From 12 ft. to 29 ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 0-3' SURFACE SOIL

Grout Intervals: From 3 ft. to 12 ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage

Direction from well? South How many feet? 75

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-16-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 437 This Water Well Record was completed on (mo/day/yr) 10-2-90 under the business name of RALPH THETZGER WELL DIGGING RALPH S. THETZGER

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send up three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.