


1 LOCATION OF WATER WELL: County: SEDGWICK		Fraction: SE 1/4 NW 1/4 NE 1/4	Section Number: 6	Township Number: T 29 S	Range Number: R 1 EW
Distance and direction from nearest town or city, street address of well if located within city? 226 WIPE HAYSVILLE, Kansas 67060					
2 WATER WELL OWNER: WILLIAM KUHN RR#, St. Address, Box #: 226 WIPE City, State, ZIP Code: HAYSVILLE, Kansas 67060				Board of Agriculture, Division of Water Resources Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 35 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 19 ft. 2. 19 ft. 3. 2-26-83 ft. WELL'S STATIC WATER LEVEL 19 ft. below land surface measured on mo/day/yr 2-26-83 Pump test data: Well water was 19 ft. after 2 hours pumping 20 gpm Est. Yield 40 gpm: Well water was 19 ft. after 2 hours pumping 20 gpm Bore Hole Diameter 9 in. to 35 ft., and 20 in. to 35 ft. WELL WATER TO BE USED AS: 5 Public water supply 1 Domestic 2 Irrigation 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) 11 Injection well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted No Water Well Disinfected? Yes (Glued) No (Clamped)			
5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC Blank casing diameter 5 in. to 19 ft., Dia 12 in., weight 2.05 lbs./ft. Wall thickness or gauge No. 250 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued (Welded) (Threaded) 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 Gauzed wrapped 8 Wire wrapped 9 Torch cut 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole) SCREEN-PERFORATED INTERVALS: From 19 ft. to 35 ft., From 19 ft. to 35 ft., From 19 ft. to 35 ft. GRAVEL PACK INTERVALS: From 13 ft. to 35 ft., From 13 ft. to 35 ft., From 13 ft. to 35 ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other SURFACE SOIL 0-3 FT. Grout Intervals: From 3 ft. to 13 ft., From 13 ft. to 35 ft., From 13 ft. to 35 ft. What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) Direction from well? NORTH WEST How many feet? 60					
FROM		TO		LITHOLOGIC LOG	
0		5		SANDY LOAM SURFACE SOIL	
5		8		SILT SAND	
8		19		CLAY	
19		35		SAND & SMALL GRAVEL	
35				SHALE	
FROM		TO		LITHOLOGIC LOG	
02		01			
17		19			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-5-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 437 This Water Well Record was completed on (mo/day/yr) 3-21-83 under the business name of RALPH THIETZGER WELL DIGGER DRILLING INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answer. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

29

R

1

EW

SEC.

6

SE

NW

NE

NE

MTP