

1 LOCATION OF WATER WELL: County: <u>Stogurk</u>	Fraction <u>8/16</u> <u>1/4</u> <u>1/4</u> <u>1/4</u>	Section Number <u>18</u>	Township Number T <u>29</u> S	Range Number R <u>1</u> EW
---	--	-----------------------------	----------------------------------	-------------------------------

Distance and direction from nearest town or city street address of well if located within city?

Same as below

2 WATER WELL OWNER: RR#, St. Address, Box # : <u>Bob Carman</u> City, State, ZIP Code : <u>8959 S. Champion</u> <u>Wich. Ks.</u>	Board of Agriculture, Division of Water Resources Application Number:
---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>47</u> ft. ELEVATION: <u>1200</u>
--	---

Depth(s) Groundwater Encountered 1 20 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 20 ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 30 gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 10 in. to 47 ft. and in. to ft.

WELL WATER TO BE USED AS:

☒ 1 Domestic	☐ 3 Feedlot	☐ 5 Public water supply	☐ 8 Air conditioning	☐ 11 Injection well
☐ 2 Irrigation	☐ 4 Industrial	☐ 6 Oil field water supply	☐ 9 Dewatering	☐ 12 Other (Specify below)
☐ 7 Lawn and garden only ☐ 10 Monitoring well				

Was a chemical/bacteriological sample submitted to Department? Yes. No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	3 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
------------------------------	----------------	-----------------	---

☒ 1 Steel

☒ 2 PVC

Blank casing diameter 5 in. to 37 ft. Dia

Casing height above land surface 12 in. weight 2.6 lbs./ft. Wall thickness or gauge No. SDR 21

☐ 3 RMP (SR)

☐ 4 ABS

☐ 6 Asbestos-Cement

☐ 7 Fiberglass

☐ 9 Other (specify below)

☐ 10 Asbestos-cement

☐ 11 Other (specify)

☐ 12 None used (open hole)

TYPE OF SCREEN OR PERFORATION MATERIAL:

☐ 1 Steel	☐ 3 Stainless steel	☐ 5 Fiberglass	☒ 7 PVC	☐ 8 RMP (SR)	☐ 10 Asbestos-cement
☐ 2 Brass	☐ 4 Galvanized steel	☐ 6 Concrete tile	☐ 9 ABS	☐ 11 Other (specify)	☐ 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

☐ 1 Continuous slot	☐ 3 Mill slot	☐ 5 Gauzed wrapped	☒ 7 Saw cut	☐ 11 None (open hole)
☐ 2 Louvered shutter	☐ 4 Key punched	☐ 6 Wire wrapped	☐ 9 Drilled holes	
☐ 7 Torch cut	☐ 10 Other (specify)			

SCREEN-PERFORATED INTERVALS: From 20 ft. to 47 ft. From ft. to ft.

GRAVEL PACK INTERVALS: From ft. to ft. From ft. to ft.

6 GROUT MATERIAL:	1 Neat cement	☒ 2 Cement grout	3 Bentonite	4 Other
-------------------	---------------	---	-------------	---------

Grout Intervals: From 2 ft. to 20 ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination:

☐ 1 Septic tank	☐ 4 Lateral lines	☐ 7 Pit privy	☐ 10 Livestock pens	☐ 14 Abandoned water well
☐ 2 Sewer lines	☐ 5 Cess pool	☐ 8 Sewage lagoon	☐ 11 Fuel storage	☐ 15 Oil well/Gas well
☐ 3 Watertight sewer lines	☐ 6 Seepage pit	☐ 9 Feedyard	☐ 12 Fertilizer storage	☐ 16 Other (specify below)
			☐ 13 Insecticide storage	

Direction from well? How many feet? None noted

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>2</u>	<u>top soil</u>			
<u>2</u>	<u>18</u>	<u>clay</u>			
<u>18</u>	<u>24</u>	<u>FINE SAND</u>			
<u>24</u>	<u>38</u>	<u>med ✓</u>			
<u>38</u>	<u>47</u>	<u>coarse ✓</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>7-8-91</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>463</u> This Water Well Record was completed on (mo/day/yr) <u>8-25-91</u> under the business name of <u>RSA</u> by (signature) <u>Samuel R. Rish</u>
