

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEDGWICK		NE 1/4 SE 1/4 SW 1/4	9	T 29 S	R 1 E
Distance and direction from nearest town or city street address of well if located within city? 8133 So. LULU WICHITA KANS.					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number: NONE			
City, State, ZIP Code :		WICHITA KANS			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 34 ft. ELEVATION: 1300			
		Depth(s) Groundwater Encountered 1. 11 ft. 2. . ft. 3. . ft.			
		WELL'S STATIC WATER LEVEL 11 ft. below land surface measured on mo/day/yr 11/26/84			
		Pump test data: Well water was . ft. after . hours pumping . gpm			
		Est. Yield 60 gpm Well water was NA ft. after NA hours pumping NA gpm			
		Bore Hole Diameter 9 in. to 11 ft., and 6 in. to 34 ft.			
		WELL WATER TO BE USED AS:			
		☒ Domestic ☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☐ 12 Other (Specify below)			
		☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes ☒ No ☐ If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes ☒ No ☐			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: ☒ Glued ☐ Clamped			
1 Steel		2 Wrought iron			
☒ 3 RMP (SR)		3 Concrete tile			
2 PVC		4 Asbestos-Cement			
☒ 4 ABS		5 Other (specify below)			
3 Fiberglass		Welded			
		Threaded			
Blank casing diameter 5 in. to 12 1/2 ft., Dia 1.59 in. to . ft., Dia . in. to . ft.					
Casing height above land surface 12 1/2 in., weight 1.59 lbs./ft. Wall thickness or gauge No. SDR 26					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		7 PVC			
3 Stainless steel		☒ RMP (SR)			
5 Fiberglass		10 Asbestos-cement			
2 Brass		11 Other (specify)			
4 Galvanized steel		12 None used (open hole)			
6 Concrete tile					
9 ABS					
SCREEN OR PERFORATION OPENINGS ARE:		8 Saw cut 11 None (open hole)			
1 Continuous slot		5 Gauzed wrapped			
☒ 3 Mill slot		6 Wire wrapped			
2 Louvered shutter		9 Drilled holes			
4 Key punched		10 Other (specify)			
SCREEN-PERFORATED INTERVALS:					
From 26 ft. to 34 ft., From . ft. to . ft.					
GRAVEL PACK INTERVALS:					
From NONE ft. to 11 ft., From . ft. to . ft.					
6 GROUT MATERIAL:		4 Other			
1 Neat cement		3 Bentonite			
☒ 3 Cement grout					
Grout intervals: From 3 ft. to 11 ft., From . ft. to . ft.					
What is the nearest source of possible contamination:		14 Abandoned water well			
1 Septic tank		15 Oil well/Gas well			
4 Lateral lines		12 Fertilizer storage			
2 Sewer lines		16 Other (specify below)			
5 Cess pool					
☒ 3 Watertight sewer lines		13 Insecticide storage			
6 Seepage pit		How many feet? 30			
Direction from well? NORTH					
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	TOP SOIL BLACK			
3	9	CLAY GRAY			
9	18	SAND MED GRAY			
18	22	SAND MED TAN			
22	34	SAND COARSE TAN			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-26-84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 104 This Water Well Record was completed on (mo/day/yr) 12-5-84 under the business name of BEARDEN PUMP & WELL by (signature) W. Bearden					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

29

R

BW

SEC.

9

NE 1/4

SE 1/4

SW 1/4

NW 1/4

SE 1/4

SW 1/4

NW 1/4

SE 1/4

SW 1/4